

Sunlight Readable Open Frame High Brightness LCD

Open Frame 7" Wide Temp -30 to 65C / 800x480 / 1500nits LED
VGA + DVI +HDMI input / Rear OSD / 110/220V AC external adapter
+Integrated external auto light sensor



Model: YOPW0700HB2WT-LS

FEATURES:

- High contrast color TFT-LCD Monitor support resolution up to 800*480.
- Power management system conforms to VESA
- DPMS and EPA Energy Star standards.
- Full consideration for touch screen installation and application.
- Universal Power adapter.
- Support DDC1 & DDC2B for Plug & Play compatibility.
- Advanced OSD control for picture quality adjustment.
- Detachable stand for wall-mounting adjustment.
- Heavy duty monitor with steel frame.
- Custom design by request.

System Specifications:

Panel Type	7-inch TFT LCD
Screen Diagonal	7-inch
Active Display Area (mm)	152.40 (H) x 91.44 (V)
Pixel Pitch (mm)	0.1905 x 0.1905
Number of Pixels	800 * 480
Contrast Ratio	400:1
Color Arrangement	R.G.B. Vertical Stripe
Brightness (cd/m ²)	1500 cd/m ²
Viewing Angle(Typ.)	65/65/70/70 (R/L/U/D)
Signal Connector	VGA + DVI + HDMI Input
Power Source	AC110 ~ 220V External Adapter
Power Management	VESA DPMS Compliant
Temperature	-30 ~ 65°C
Plug & Play	VESA DDC 1/2B

Photo Gallery:



Mechanical Drawing:

