

BHK Series



2U DUAL LCD Keyboard DRAWER

2U Rackmount Dual 2 x 19" LCD 1280 x 1024 integrated with 101-key pull out backlit keyboard and touchpad, VGA x 2, DVI-D x 2, S-Video x 2, Composite x 2, SDI in/Out x 2, for each display 3.5" (2U rack height) x 17.5" W x 26" D / 53 lbs 115/230 VAC, 50/60Hz, 100W Max Temperature: MIL-STD- 810E (501.4, 502.4), Humidity: MIL-STD-810E (507.2), Altitude: MIL-STD-810E (500.3), Vibration: MIL-STD-810E (514.4), Shock: MIL-STD-810E (516.4)

Model: BHK2D119e-SDI

FEATURES

- Temperature: MIL-STD- 810E (501.4, 502.4), Operating: 0 ~ 50°C Non-Operating: -40 ~ 70°C
- Humidity: MIL-STD-810E (507.2), Relative Humidity: 5% to 95% operating, non-condensing
- Altitude: MIL-STD-810E (500.3), Operating: 15,000 ft (4571.8 m), Non-Operating: 40,000 ft (12,192 m)
- Vibration: MIL-STD-810E (514.4), Operating: 10 to 500 Hz 1.04 g (RMS)
- Shock: MIL-STD-810E (516.4), Operating: 15 G, 8 ms 1/2 sine, Non-Operating: 40 G, 8 ms 1/2 sine, Drop: 4" stand alone, 39" transit drop in transit case

Standard 115/230 VAC, 50/60Hz, 100W Max



OPTIONS

- 23" Display
- 18-36V DC Input
- Analog VGA, DVI-D, HD-SDI, S Video- In for each display
- 5-minute UPS backup
- Angled LCD Brace for space constrain

Optional for 28VDC input



SPECIFICATIONS

Video Input	VGA x 2 , DVI-D x 2 , S-Video x 2, Composite x 2, SDI in/Out x 2
Weight	53 LBS
Dimensions	2U, 3.46" x 17.76" x 25.89" /88mm x 451.2mm x 657.6mm (H x W x D)
Power Supply	115/230 VAC, 50/60Hz, 100W Max
Construction	Heavy Duty Steel Frame
Keyboard	81-backlight keys with 5 levels of adjustable brightness with Touchpad
Approvals	CE, FCC, UL, CCC, ROHS

Display	2x 19", 5:4
Resolution	1280x1024
Display Adjustment	Individual brightness, contrast, color temperature adjustments
Display Deployment	Displays rotate up from stowed position, Rotate & open via butterfly action and slide to center the two displays on the operator
Display Tilt	Displays tilt ~10° from vertical for optimal operator positioning