

# All in one PC Widescreen Display Stand Alone

Passivation of coated stainless steel 304 (No Finger prints)  
 All in one PC Widescreen Display Stand alone Kiosk 21.5" LCD  
 monitor, 1920 x 1080, 250 nits, Mother Board: Gigabyte B75TN  
 embedded mother board, i5-3470T (3M Cache, up to 3.60  
 GHz)+Flex wall mount., 4GB Memory and 500GB HDD.  
 Dual LAN/6 x USB with Capacitive Touch 2mm

**Model: BKS2150i5SS-PCT**

iTech Company's All-in-one PC Widescreen Display Stand Alone Kiosks are ideal for office or commercial buildings to facilitate and automate some tasks. It can be used as an innovative signage system or self-guided information facility to improve efficiency, security, energy savings and overall work environment.

## Features

- Stand-alone kiosk
- Heavy-duty coated stainless steel construction
- High brightness and high contrast ratio options
- Capacitive touch screen
- Broad viewing angle
- Flex wall mount
- High resolutions
- Embedded motherboard with Intel processor
- Dual LAN and 6x USB

## Specifications

Viewable Size Image	21.5"(16:9)
Active Display Area(mm)	476.64(H) x 268.11 (V)
Number of Pixels	1920 x 1080
Contrast Ratio	5000 : 1
Display Color	16.7 million
Brightness(cd/m)	300
Viewing Angle	R/L178° x U/D178°
Recommended Resolution	1920 x 1080
Response time	16 ms
Life time	30,000/hr
Signal Input	1 x VGA, 1 x DVI

## Mechanical

Operating Temp.	0°~50°C
Humidity	20~80% RH
Store Temp.	-20°~55°C
Dimensions(mm)	600(L)x320(W)x1200(D)
Material	SUS
Door lock	1 SET

## Accessories

• DVI Wire x 1	
• 3.5" Audio Wire x 1	
• Power Core x 1	

## Power

Power Input	110V/220V AC
Power Consumption	95W

## IP68 Glass

Glass	AR Coating 2mm
-------	----------------

## System Specifications

CPU	Micro ATX MATMH61+i5-3470t
RAM	DDR3 SDRAM 4G
Storage	500G HDD--2.5"
USB Port	2 x USB 2.0 + 1
PC Audio output	Realtek ALC662
Speaker Output	2 x 10W internal speaker
LAN Port	2x RJ-45 10/100/1000
WIFI	IEEE 802.11b/g/n



