

KCPC Series Full Metal Industrial Panel PC









15" Fanless full industrial panel PC with 5 wires resistive touch screen (Intel Atom 3.5" mainboard + full metal standard panel PC (black fornt + sliver back) + DC in external power adapter + Rack for 2.5" HDD + VESA mounting 100 x 100mm + Resolution: 1024 x 768 dpi)




MODEL: KCPC1500-AT


FEATURES:

- **Elegant Sliver / Black metal chassis design**
- **Powerful performance but low power consumption**
- **Fanless design and compact solution**
- **Widescreen solution for 21.5" and 24"**

	CPU Performance	
	Energy Efficiency	
	Touch Function	
	Dissipation Design	Fanless, External heat sink
	Housing Design	Metal Chassis Design



Elegant silver / black metal chassis



Compact design



I/O ports located in the back bottom side



Black metal chassis design from 15" to 21.5"



Sliver metal chassis design from 15" to 24"

Widescreen solution for 21.5" & 24" (16:9)



High Uniformity

SPECIFICATIONS:

Display	Size / Aspect Ratio	15" TFT (4:3)
	Backlight	LED
	Resolution	1024 x 768
	Colors	16.2 M
	Luminance (cd/m2)	400
	Contrast Ratio	700:1
	Viewing Angle (H/V°)	160/160
	MTBF (hrs)	50,000
	Touch Screen	5-wire resistive
	Dimension (W x H x D, mm)	TBD
	Weight (kg)	TBD
	Color	Black (front) / Sliver (back)

CPU	Intel Dual Core Atom D2550 1.86GHz	
Chipset	Intel NM10	
Memory	1 x DDR III SODIMM up to 4 GB	
Power Supply	DC in 12V external power adapter	DC in 9V ~ 36V external power adapter
I/O Ports (Default)	1 x RS232, 2 x GLAN, 2 x USB, 1 x VGA, 2 x SATA socket	1 x RS232, 2 x GLAN, 2 x USB, 1 x VGA, 1 x SATA socket, 1 x Power terminal block
I/O Ports (Optional)	Extra 1 x RS232, 1 x RS232/422/485, Extra 2 x USB, 1 x Line-out, 1 x Mic-in	Extra 1 x RS232, 1 x RS232/422/485, Extra 2 x USB, 1 x Line-in, 1 x Line-out, 1 x Mic-in
Expansion	1 x CF card socket, 1 x Mini PCIe slot	1 x C Fast card socket, 1 x Mini PCIe slot
Operation Temperature	0°C ~ 45°C	
Storage Temperature	-10°C ~ 70°C	
Relative Humidity	0% ~ 90% non-condensing	
OS Support	Win 7 Pro, Embedded 7	
Installation	VESA mount 100 x 100 mm	
Optional Items	External DVD-RW driver, RFID sensor, Memory, Storage devices, WiFi, OS Support	

MECHANICAL DRAWING:

Not Available

