RUGGED TOUCH LCD MONITOR


24" TFT LCD display, Aluminium front bezel with panel mount Projective capacitive touch screen 1920 x 1080 resolution 300nits brightness Standard port for 1 x VGA, 1 x DVI 1 x 100~240V AC-DC power adapter

Design to meet MIL-STD-810, 461 & 462
Lead time 6-8 weeks after approval of drawings

Model: NPMW2400-PCT



MECHANICAL DRAWING:



SPECIFICATIONS:

Housing Construction

Rugged steel construction, metal chassis with solid aluminum front bezel

IP Rating

IP-65 Water-resistant rated at front

LCD Display size

23.6" TFT LCD color display

LCD Resolution

1920 x 1080 resolution 16 : 9 aspect ratio

Brightness of LCD (Luminance)

300 cd/m2 high brightness

Number of Colors:

16.77 millions colors.

View Angle:

Left and right: 170 degree; Up and down: 160 degree

Contrast Ratio:

1000:1

Optical Response Time:

5ms

Life of lamp tubes:

50,000 hours

Color of housing:

Standard : Black

Please specify the color if another color is requested.

Touch Screen: (optional)

5-Wire Resistive Touch screen, 4096 x 4096 high resolution

Touch Screen interface : (optional)

USB interface or serial interface at your request.

Wall-mount standard

Support VESA-100 wall-mounting Support panel mount

I/O Port:

Support VGA and DVI ports.

OSD control buttons:

On-Screen-Display buttons and Power switch button are located at the rear side. (If OSD buttons are preferred to locate on another side, please specify on your order.) This OSD buttons can control screen position Up, Down, Left, Right, Brightness, Contrast ratio, menu, power switch.

Vibration and Shock resistant:

Meets industrial and vehicle vibration and shock standards

Power Input:

AC 100-240V input power source Option: DC-DC power adapter

Operation Temperature:

0~+50 oC

Storage Temperature:

-20~+60 oC



i-Tech Company LLC
TOLL FREE: (888) 483-2418 • EMAIL: info@iTechLCD.com • WEB: www.iTechLCD.com