

Large Touch LED Monitor

46" SPVA LCD Display with LED Backlighting Optical
6 Point Multi-Touch

Model: OCHW4600HD-6T



With high resolution and multi-touch screen functionality, this LED monitor display delivers exceptional colour performance, wide viewing angles, and accurate touch response. It also supports various inputs including HDMI, DVI-D, VGA, S-Video, and BNC Composite. Either it is an Interactive Digital Signage, Kiosks, Instore Retail, Gaming and Interactive Presentations, it is an ideal solution for these applications.

Features

- LED Backlighting
- 6 Point Multi-Touch Screen
- High Resolution
- Supports Various Inputs including HDMI, DVI-D, VGA, S-Video, and BNC Composite
- OPS Expansion Slot
- Sleek Design

Product Specifications:

Size/Type	46 inch Diagonal/ SPVA LCD Display with LED Backlighting
Touch Technology	Optical 6 Point Multi-Touch
Contents of Packaging	User's Manual, AC Power cord, Wireless Remote, Batteries, 15-pin RGB Cable, CD-ROM, Setup Sheet & Driver CD
Brightness	550-700 cd/m ² (Nits)
Contrast Ratio	4000:1
Colors	more than 16 million (depending on video card used)
Optional	TV Tuner, Internal PC, External Speakers, Stand
Dimensions (W x H x D)	Net (with stand): 41.6" (W) x 25.4" (H) x 9.4" (D) / 1055.4 x 645.7 x 240 mm Net (without stand): 41.6" (W) x 24" (H) x 2.5" (D) / 1055.4 x 608.6 x 64.5 mm
Input	HDMI, DVI-D, DisplayPort, VGA, 5 BNC, S-Video, BNC Composite
Input Signal	Video: ANALOG RGB 0.7 Vp-p / 75 Ohms Separate sync: TTL Level (Positive/Negative) Composite sync: TTL Level (Positive/Negative) Composite sync on green: (0.3Vp-p negative 0.7Vp-p positive)
Limited Warranty	3 year including backlight
Operating Altitude	3000m/9842.5 ft.
Operating Humidity	20-80%
Operating Temperature	0-50 C/32-122 F
Pixel Pitch	0.53mm
Power Consumption	(typical) On: 120W, Power Savings Mode: <.5W
Resolution	1920 x 1080
Storage Altitude	40,000 ft. / 12,192m
Storage Humidity	10-90%
Storage Temperature	-20-65 C/-4-149 F
VESA Hole Configuration Spec.	300 x 300 mm (4 hole)
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R)
Voltage Rating	AC 100-120V / AC 220-240V @ 50/60 Hz
Weight	Net without stand: 60 lbs.
Output	BNC Composite, DisplayPort, DVI-D Audio: Stereo Mini Jack, External Speaker Jack (2) External Control: RS-232C, IR Remote
Additional Features	Power Management Plug and Play (DDC/CI DDC2B) PIP (Remote) Multi level Zoom, FullScan, 6 axis color CableComp TileMatrix TileComp Screen Saver Rapid Response, Video Ready (no tuner) Infrared remote control included

iTechLCD, reserves the right to change any of the information contained on this document without notice. We also reserve the right to discontinue, limit production or distribution of this our any other iTechLCD product.

