

USB HUB DB15 LCD Console Drawers

Dual Slides 1U 17.3" 1920 x 1080 native resolution (can support up to 1920 x 1200 resolution through our AD board)Widescreen Rackmount LCD Keyboard Console Drawer, DB15 8 Ports USB KVM (Support USB HUB 2.0 and touch screen enable function)

Model: ADRW1730HD-8e



USB Port for device access

LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades. The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation.

Available with 17.3" A-Grade LCD panels, combo DB15 8 or 16 port integrated KVM switch & with an option remote IP console. Support USB HUB 2.0 and touch screen enable function.

FEATURES

- Support USB interface, VGA-USB.
- Front 1x USB, Rear 2x USB 2.0 Type A ,Sharing USB peripheral Device for computer (ex, flash disk ,hard driver, KB/Mouse).
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Access Control List (ACL) security function for up to 8 independent user accounts.

Optional Remote IP Access

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



SPECIFICATIONS

Direct no. of Computers	8	
Maximum no. of Computers	8	
LCD	Size	17.3"
	Backlight	LED
	Resolution	1920*1080 Full HD (support resolution up to 1920x1200)
	Max. color	262K
	Luminance	300cd/m2
	View Angel (H/V)	140 / 120
	Contrast Ratio	3000 : 1
Port Selection	Push Button, OSD or Hotkey	
Expansion Slot	Option for remote IP access	
USB HUB	Yes, Front 1x USB 2.0 , Rear 2x USB 2.0 Type A for USB Peripheral Device	
Touch Screen	Yes, for option (Driver needed)	
KB/Mouse Emulation	USB	
Rack Depth	500mm to 1100mm (rack cabinet front rails to rear rails)	
Power	100-240V AC 50/60Hz via IEC Type power cord	
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP	
Physical Dimensions / Net Weights	448x42x600mm (WxHxD) / 12.5KG	
Packing Dimensions / Gross weights	720x190x800mm (WxHxD) / 18.5KG	
Accessory		
1.8meter IEC Type Power Cord		

MECHANICAL DRAWINGS

Rear of ADRW1730HD-8e



Rear of ADRW1730HD-16e

