2U Rack mount SamSung 19" TFT LCD monitor keyboard drawer / KVM switch

RKP 219, RKP219-801 RKP219-1601

Features:

- Unique monitor flip up design allows viewing through closed glass door of cabinet
- Adjustable mounting brackets from 15.4" to 31.1" (390 to 790 mm) (front to rear 19" mounts). Suitable for 30" to 39.4"(750 to 1000mm) deep 19"cabinet
- May fitted into an 31.52"(800mm) deep rack by the use of extended brackets on request
- Built-in on screen display controlled by integral membrane switches
- Front access lock for security
- Standard D-sub 15-pin VGA input connector
- Slide rails have two fixed positions to prevent movement of the keyboard
- Supplied with 12V 5A remote power adapter(Single power source)



With KVM Features only:

- Multi-platform-mix PCs, SUNs, IBMs, HPs, Compag & DELL
- Support 8 characters password protection & search PC server name
- Cascades for use with up to 128 servers
- New keep alive feature safeguards server for power loss to the switch
- Built-in microprocessor emulation for each port boots up process
- Auto scan-mode for monitoring your servers at intervals 5 to 99s
- **Hot-pluggable** when adding or removing PC w/o powering down the switch
- Name you server up to 16 characters long
- Supplied w/12V 1A remote power adapter(single power source)
- Supplied with 8 screened cables 6ft long
- No software needed & all mounting hardware included

Specification

Monitor

Panel: 19" LCD panel

Display type: TFT / LCD active matrix color

Resolutions: 1280 x 1024
Response time: Tr=15ms/ Tf=10ms
Contrast ratio: 500 : 1 typical
Brightness: 250 cd/m² typical

Pixel pitch: 0.098mm (H) x 0.294mm (W)
Panel color: 16.7 million display colors
Viewing angle: 170° (Horiz.)/ 170° (Vert.)
Storage temp. -20° C to 65 ° C

Storage temp. -20° C to 65 ° C
Operating temp. 0 ° C to 50 ° C
MTBF 20,000 hours

KVM

Computer connectors: 8/16

Connector: 15-pin HDB type, Keyboard, mouse, all-in-1

Cascade level: 8
Max. access PCs: 128
Input VGA resolution: 1,920 x 1,440

Keyboard Selection

- 1: Notebook type keyboard with touch pad mouse
- 2: Cherry keyboard with trackball
- 3: Compact keyboard integrated with Optical trackball

Power supply

Remote adapter: 110V - 220V AC Input 12V 5A Output

Adapter Size: 4.3"(L) x 2.4" (W) x 1.2"(H)

(108x61x30mm)


Cable length from mains plug to adapter: 6ft (182cm)

Cable length from adapter to unit: 6ft (180cm)
Safety approval: UL, CE

Mains plug options available

Weight

<u>Model</u>	KVM	Net / Gross weight
RKP217	Non	30.8lbs / 46.2lbs (14kg/21kg)
RKP217-801	8 port	33.0lbs/ 50.6 lbs (15kg/23kg)
RKP217-1601	16 port	35.2lbs / 52.8lbs(16kg/24kg)



Product dimension--- 17.3"(W) x 3.5"(H) x 23.6"(D) (439x88x600mm)

Packing dimension--- 29.0"(L) x 22.7"(W) x 7.1"(H) (735x575x180mm)