

Military Rugged Rackmount LCD Drawer

1U 19" Rackmount Rugged LCD Keyboard drawer 1280 x 1024,
350nits, Durable 88-key keyboard, Front EMC glass, DC 9-36DC
input, with 8-ports DVI KVM (Standard DVI I/O)

Operation temp: -20 to 55C

Storage temp: -30 to 65C

Humidity: 10% - 90%, non-condensing

Shock: 10G acceleration (11ms duration)

Vibration: 17 to 500Hz 1G PTP

Model: AMil-1900-D8e




FEATURES

- Meet MIL-STD-810F/G standard
- 1U 17" or 19" LCD Console Drawer, wide operation temperature support 1280 x 1024 resolution
- Buildin 8 port DVI-USB KVM switch
- Front 1x USB, Rear 2x USB 2.0 Type A, Sharing USB peripheral Device for computer (ex, flash disk, hard driver, KB/Mouse)
- Sealed 104-keys IP65 silicone keyboard and touchpad with backlight
- MIL connector for power input
- Support USB 2.0 Keyboard & Mouse
- Self-locking and auto release rails for ultra convenience

Option

- High brightness LCD panel, up to 1000 nits
- Front AR or EMC glass protect screen
- Touch screen



SPECIFICATIONS

Direct no. of Computers		8
KVM Connectors		8
LCD	Size	19"
	Backlight	LED
	Resolution	1920x1024
	Max. color	16.7M
	Luminance	450cd/m2
	View Angel (H/V)	170 / 160
Contrast Ratio		1000 : 1
Port Selection		Push Button, Hotkey
USB HUB		1x Front , 2xRear USB 2.0 Type A for Peripheral USB Device
Touch Screen		Yes, for option
KB/Mouse Emulation		USB
Rack Depth		500mm to 1100mm (rack cabinet front rails to rear rails)
Power		DC 9-36V DC input
Environment (MIL-STD-810G)		Operation temp: -20 to 55°C (MIL-STD-810, Method 501.5 & 502.5)
		Storage temp: -30 to 65°C (MIL-STD-810, Method 501.5 & 502.5)
		Humidity: 10% - 90%, non-condensing (MIL-STD-810, Method 507.5)
		Shock/Vibration: Procedure VI, 50G @ 11ms (MIL-STD-810, Method 516.6)
		Altitude: 10,000 ft Operational, 30,000 ft Storage (MIL-STD-810, Method 500.5)
Physical Dimensions / Net Weights		482x44x635mm (WxHxD) /14KG
Packing Dimensions / Gross weights		(WxHxD) /KG
Accessory		
1 x 1.8 Power Cord with lock connector		

MECHANICAL DRAWINGS

