

Rack Mount Flip-down Display Drawer

19" 1280 x 1024 VGA, DVI-D, Audio input and built in 2 watts speakers Adjust Angle 0-104Degree 508mm/20" deep

Model: ANP119UM



FEATURES:

- 1U Flip-down 19 inch rack mountable
- 19 inch 1280 x 1024 resolution
- DVI-D, VGA, Audio input
- Heavy duty steel chassis construction
- Front osd control buttons to optimized display
- Build in 2x 2watts stereo speakers
- Adjust angle 0°~104°

OPTION:

- Composite video input
- HDMI or Display port input
- 3G / HD / SD-SDI broadcast grade input
- DC 9~36 V power input
- AR Hardness glass
- Touch screen

SPECIFICATIONS

LCD CHARACTERISTICS	
Screen Size	19"
Backlight Type	LED
Resolution	1280*1024
Contrast Ratio	1000:1
Brightness (cd/m2)	350
View Angles (H/V)	170/160
Pixel Size (HxV) mm	0.294x0.294
Max. Color	16.7M
MTBF (Hrs.)	50,000

INPUT SIGNALS	
DVI-D	DVI-D 24Pin Connector (Female)
VGA	D-SUB 15Pin Connector (Female)
Audio	3.5" Jack
Power Input	Standard IEC Inlet
Touch-USB (option)	USB A Type connector
Touch-RS232 (option)	D-SUB 9P connector (Female)

POWER SPECIFICATIONS	
AC Power Input	Standard IEC Type Power Cord with Internal Power adapter, 100-240V AC Input
Wide Range DC Power Input (option)	Screw Type Terminal Block with internal wide Range DC 9-36V power module

USER CONTROL INTERFACE	
Power ON / OFF via Front Button	
Power Mode Status LED indicator	
OSD (On Screen Display) Buttons	

MECHANICAL AND ENVIRONMENT	
Height	1U Foldable
Rack Depth	20" to 36" (cabinet front rail to rear trail)
Mounting	Rack Mount with tilt adjustment
Construction	Metal Housing
Operating Temperature	0 - 50 deg. C
Operating Humidity	5% - 95% (non -condensing)
Anti-Vibration	5 - 500 Hz / 1 Grms PTP
Anti-Shock	15G / Peak (11 ms)
Physical Dimension (WxHxD)	448*44*508 (mm)
Packing Dimension (WxHxD)	790*190*580 (mm)
Net Weight / Gross Weight	17.5 / 21 (KGs)
Certification and Approvals	CE / FCC / RoHs

DRAWINGS

