



Wide 7 in WVGA HMI panel PC. Intel ATOM N2600 (NM10 chipset), Onboard 2GB DDR3 memory, 32GB SSD, 1x 1.8in SATA2 Drive Bay. Features Aluminum Die-cast chassis, Fanless design, Front IP65, 1x Internal SD slot, 2x USB 2.0, 2x COM, 2x GbE LAN, Capacitive touch screen, 9~36VDC power input with adapter.

APCW0700-AT



FEATURES:

- 7" TFT-LCD Projected Capacitive Touch. Flat Front Panel meets IP65
- Intel Atom Cedar View N2600 1.6GHz Dual Core CPU
- Aluminum Die-Casting Chassis, Fanless Design
- Aluminums Heat-Sink for thermal dissipation
- Easily Accessible Storage, Expansion slot support
- 9~36V DC input with Professional Terminal Block



SPECIFICATION:

SYSTEM		TOUCHSCREEN (option)	
Processor	Intel Atom Cedar View N2600 1.6GHz Dual Core Processors	Type	Resistive Touch / Projected Capacitive Touch (for P model)
System Memory	Onboard DDR3 2GB 800 MHz	Light Transmission	80% / 90% (for P model)
System Chipset	Intel NM10	Interface	RS-232 / USB (for P model)
IO Port		POWER SUPPLY	
USB	2 x USB 2.0 type A, USB4/5	Power Input	9~36V DC
Serial/Parallel	1x RS-232/422/485 DB-9, COM1, Default RS-232 1 x RS-232 DB-9, COM2	MECHANICAL	
Audio	1 x Line out phone jack	Construction	Sliver aluminum front bezel and chassis
LAN	2 x GbE RJ-45	IP Rating	IP65 front panel
Power	3 pins terminal block connector, DC Power input	Mounting	Panel mounting, VESA 75 x 75
Storage Space		Dimension	202mm x 149mm x 39mm
HDD	1 x 2.5" SATA 2	Net Weight	2.3
Movable device	x Internal SD slot	ENVIRONMENTAL	
Expansion		Operating Temperature	0~50 OC
On board expansion bus	1 x Mini-PCIe half size	Storage Temperature	-20~60 OC
Storage Humidity		Storage Humidity	10 to 90% @ 40°C, non-condensing
Display		Certificate	CE / FCC Class A
Display Type	7" TFT-LCD	Operating System Support	
Max. Resolution	800x480	Windows XP pro Windows XP Embedded Windows Embedded CE6.0 Windows 7 pro for Embedded Windows Embedded standard 7 (Win 7 support 3D Graphic function)	
Max. Color	262k		
Brightness	350		
View Angle	H: 140/V: 110		



DIMENSION:

