

# Industrial PANEL PC

12.1" SVGA Fanless HMI barebone with Atom N2600  
1.6G CPU, 2GB DDR3 memory, resistive touch screen,  
9~36VDC input with adapter, Aluminum chassis.

## APC1210-AT



### FEATURES:

- 12" LCD Panel
- Flat Front Panel with IP65 Design
- Solid Aluminum Die-casting Chassis
- Intel Atom N2600 processor,  
Dual Core Low Power Fanless System

### SPECIFICATION:

SYSTEM		TOUCHSCREEN (option)	
Processor	Intel Atom Cedar View N2600 1.6GHz Dual Core Processors / Intel Atom D2550 1.8GHz (Optional)	Type	Resistive Touch / Projected Capacitive Touch (for P model)
System Memory	Onboard DDR3 2GB 800 MHz / 4GB (Optional)	Light Transmission	90%
System Chipset	Intel NM10	Interface	USB
Power Consumption	18W	<b>POWER SUPPLY</b>	
<b>IO Port</b>		Power Input	9~36V DC
USB	2 x USB 2.0 type A, USB4/5	<b>MECHANICAL</b>	
Serial/Parallel	x RS-232/422/485 DB-9, COM1, Default RS-232 1 x RS-232 DB-9, COM2	Construction	Sliver aluminum front bezel and chassis
Audio	1 x Line out phone jack	IP Rating	IP65 front panel
LAN	2 x GbE RJ-45	Mounting	Panel mounting, VESA 100 x 100
Power	3 pins terminal block connector, DC Power input	Dimension	319mm x 245mm x 52mm
<b>Storage Space</b>		Net Weight	2.5
HDD	1 x 2.5" SATA 2	<b>ENVIRONMENTAL</b>	
Movable device	x Internal SD slot	Operating Temperature	0~50 OC
<b>Expansion</b>		Storage Temperature	-20~60 OC
On board expansion bus	1 x Mini-PCIe half size	Storage Humidity	10 to 90%@ 40°C, non-condensing
<b>Display</b>		Certificate	CE / FCC Class A
Display Type	12" TFT-LCD	<b>Operating System Support</b>	
Max. Resolution	800x600	Windows XP pro Windows XP Embedded Windows Embedded CE6.0 Windows 7 pro for Embedded Windows Embedded standard 7 (Win 7 support 3D Graphic function)	
Max. Color	16.2M		
Brightness	330		
View Angle	H:160° / V:140°		



**PHOTO GALLERY:**



**DIMENSION:**

