AS Series Declaration of Conformity to MIL-STD

Cradlepoint, Inc. hereby declares that the following products:

MODEL: AMil-1900-D8e

Have demonstrated compliance with the following specifications and standards:

Evidence of compliance is demonstrated by test reports to the following applicable standards.

Applicable Specifications / Standards

Standard title, specification number, and number of the test report

MIL-STD 810G Method 507.5 Humidity Section 2.6.3 Procedure II

MIL-STD 810G Method 514.6, Operational vibration Annex C, 2.1 - Category 4

Longitudinal: 10-500Hz, 0.74g; Transverse: 10-500Hz, 0.20 g; Vertical: 10-500Hz, 1.04g; 1 hour/axis, 3 axis

MIL-STD 810G Section 2.2.2 Operational Shock, Procedure 1

Terminal peak sawtooth pulse, 40g, 11ms, 2 shocks/face, 6 faces

MIL-STD 810G Section 2.2.2 Non-Operational Shock, Procedure 5

Crash Haz Terminal Sawtooth pulse, 40g, 11ms, 2 shocks/face, 6 faces

IEC 60068-2-27 (Shock)

Sine Wave, 100g 11ms, 3 shocks/face, 6 repetitions

IEC 60068-2-32 (Drop)

6 faces, 2 drops/face

EN 61373 Random vibration, Category 1, class B

X: 5-20Hz, 0.0144 m/s², 20-150Hz -6dB/Oct, 0.70m/s², Y: 5-20Hz, 0.0060 m/s², 20-150Hz -6dB/Oct, 0.45m/s²,

Z: 5-20Hz, 0.0298 m/s², 20-150Hz -6dB/Oct, 1.0m/s², Rotated on vertical plane; operating; 10min/axis

EN 61373 Non-operational vibration, Category 1, class B

 $X:\ 5\text{-}20\text{Hz},\ 0.461\ \text{m/s}^2,\ 20\text{-}150\text{Hz}\ \text{-}6\text{dB/Oct},\ 0.70\text{m/s}^2,\ Y:\ 5\text{-}20\text{Hz},\ 0.192\ \text{m/s}^2,\ 20\text{-}150\text{Hz}\ \text{-}6\text{dB/Oct},\ 0.45\text{m/s}^2,\ 0.45\text{m/s}^$

Z: 5-20Hz, 0.968 m/s², 20-150Hz -6dB/Oct, 1.0m/s², Non-operating; 5 hours/axis

EN 61373 Non-operational shock

3 shocks/face, X:50m/s², 30ms; Y:30m/s², 30ms; Z:30m/s², 30ms

Environment (MIL-STD-810G)

Operation temp: -20 to 70°C (MIL-STD-810, Method 501.5 & 502.2) Storage temp: -30 to 80°C (MIL-STD-810, Method 501.5 & 502.2) Humidity: 5% -95%, non-condensing (MIL-STD-810, Method 507.5)

Humidity: 5% -95%, non-condensing (MIL-STD-810, Method 507.5)
Shock/Vibration: Procedure VI, 50G @ 11ms (MIL-STD-810, Method 516.6)
Altitude: 10,000 ft Operational, 30,000 ft Storage (MIL-STD-810, Method 500.5)

Declaration

I hereby declare that the contents of this form are true and correct, that the product mentioned above complies with the relevant above mentioned standards and all products supplied under this declaration will be identical to the product identified above.