

# DVI LCD Console Drawers Screen Rotate Version

24.1" FHD LCD Console Drawer  
with Integrated 8 port DVI KVM switch and USB-DVI

Model: ASKW2400SX-D8e



i-Tech's range of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades. The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation. Available with 21.5" or 23.8" Full HD A-Grade LCD panels, integrated 8 port DVI KVM switch, USB-DVI & Audio Support USB HUB 2.0 and touch screen enable function.

## FEATURES:

- Facilitated by screen rotate function
- Support USB-DVI & Audio interface
- Support digital DVI and analog VGA input signal
- Front 1x USB, Rear 2x USB 2.0 Type A, Sharing USB peripheral Device for computer (ex, flash disk, hard driver, KB/Mouse)
- Additional two USB console port to add local KB/Mouse
- Build in 2x 2 watts stereo speakers
- Durable 104-key keyboard and touch pad
- Quick and simple installation
- Self-locking and auto release rails for ultra-convenience



Rear of KVM ASKW2400SX-D8e

## SPECIFICATIONS

<b>Direct no. of Computers</b>		8	
<b>Maximum no. of Computers</b>		8	
<b>LCD</b>	Size	24.1 inch FULL HD display	
	Backlight	LED	
	Resolution	1920 x 1200 Native Resolution	
	Max.color	16.7M	
	Luminance	250cd/m2	
	View Angel (H/V)	178 / 178	
	Contrast Ratio	1000 : 1	
<b>Port Selection</b>		Push Button, OSD or Hotkey	
<b>USB Local console</b>		Yes , USB x2 for KB/ Mouse	
<b>USB HUB</b>		1x Front , 2xRear USB 2.0 Type A for Peripheral USB Device	
<b>Touch Screen</b>		Yes , for option ( Driver needed )	
<b>KB/Mouse Emulation</b>		USB	
<b>Rack Depth</b>		600mm to 1300mm ( rack cabinet front rails to rear rails )	
<b>Power</b>		100-240V AC 50/60Hz via IEC Type power cord	
<b>Environment</b>		Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration ( 11ms duration) Vibration: 17 to 500Hz 1G PTP	
<b>Physical Dimensions / Net Weights</b>		448 x 44 x 790mm (WxHxD) / 19.5KG	
<b>Packing Dimensions / Gross weights</b>		580 x 195 x 840mm (WxHxD) / 23KG	
<b>Accessory</b>			
1.8meter IEC Type Power Cord			
<b>Option Relate Item</b>			
ADV16	1.8meter DVI-D Cable	AAUC6	1.8meter USB Cable
AUSB6	1.8meter Audio Cable		



Lift the display




Display rotate to the right



Operating position

**DRAWINGS:**



Rear of KVM ASKW2400SX-D8e

