



15" LCD 1024 x 768 (AUO panel G150XG01V3), 1000 nits, 700:1, DC 9~36V power input, 5-side IP65 vesa mount with Pig Tail cables 6ft long for S-Video and HDMI and Power 12Vw/ OP Temp -30 ~ 85°C

Model: AS1500HBIP-C

FEATURES:

- 15" LCD 1024 x 768 (AUO panel G150XG01V3)
- 1000 nits, 700:1
- DC 9~36V power input
- Side OSD with VESA mounting 75x75 and 100x100mm
- OP temp -30 to 85 degree C

SPECIFICATIONS:

Display	Viewing Size Image	15"
	Active Display Area (mm)	304.1 (H) x 228.1 (V)
	Pixel Pitch (mm)	0.297 (H) x 0.297 (V)
	Resolution	1024 x 768
	Contrast Ratio	700 : 1 (typ.)
	Color	16.7M
	Brightness	1000nits
	Viewing Angle	-70~70 (H) ; -60~60 (V)
	Recommended Resolution	1024 x 768 @ 60H, 75Hz
	Signal Connector	S-Video, HDMI
Power	Source	DC 9~36V power input
	Consumption	25W typical, normal operation
	Management	VESA DPMS Compliant

APPLICATIONS:



MECHANICAL DRAWING:

