

IP65 Waterproof High Brightness Dual Slide LCD Keyboard



1U 17" 1280x1024 Single Slide LCD Keyboard
 HDMI input, 1000 nits, operating temp. -30~85C, aluminum chassis, IP65
 Display and IP65 Keyboard combo PS/2 and USB Optional with Optical
 Bonding.

8ports Combo USB and PS2 KVM
 16ports Combo USB and PS2 KVM

Model: AVP117WTHB Series

These ranges of LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades. The self-locking rails when in the fully extended open position and the ultra-convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation. Available with 17" A-Grade LCD panels, combo DB15 single, 8 or 16 port integrated KVM switch. LCD module front face compliant with IP65 waterproof grade, keyboard and touch pad module IP68 grade for tough environment applicati

FEATURES:

- Support combo interface, VGA-USB& VGA-PS2.(single port VGA-USB)
- Short depth design suit for mobile rack and limited space.
- LCD front face IP65 waterproof grade.
- Silicon 98-key keyboard and touch pad IP68 waterproof grade.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.



SPECIFICATIONS

Part no.	AVP117WTHB	AVP117WTHB-8e	AVP117WTHB-16e
Direct no. of Computers	1	8	16
Maximum no. of Computers	1	232(Daisy Chain)	240(Daisy chain)
LCD	Size	17"	
	Backlight	LED	
	Resolution	1920x1024	
	Max color	16.7M	
	Luminance	1000cd/m2	
	View Angel (H/V)	176 / 170	
	Contrast Ratio	1000 : 1	
Port Selection	N/A	Push Button, OSD or Hotkey	
USB Local console / Expansion Slot	N/A		
KB/Mouse Emulation	USB	USB & PS2	
Rack Depth	380mm to 620mm (rack cabinet front rails to rear rails)		
Power	100-240V AC 50/60Hz via IEC Type power cord		
Environment	Operation temp: -30°C to 85°C Storage temp: -20°C to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP		
Physical Dimensions / Net Weights	448x42x580mm (WxHxD) /14KG		
Packing Dimensions / Gross weights	605x168x700mm (WxHxD) /17KG		
Accessory	1.8meter IEC Type Power Cord (1.8 meter VGA & USB A Type Cable for AVP117WTHB)		

DRAWING

Rear of AVP117WTHB



Rear of AVP117WTHB-8e



Rear of AVP117WTHB-16e

