

Combo DB15 LCD Console Drawers

17" A-Grade LCD panels, combo DB15 single, 8 or 16 port integrated KVM switch & with an option remote IP console. 220VDC Terminal Block "+" and "-".

Model: AVP117 Series (220VDC)

These LCD console drawers provides a variety of features that simplify to access servers to making system monitoring, troubleshooting and software upgrades. The self-locking rails when in the fully extended open position and the ultra convenient auto lock release when the LCD panel is closed, make for simple and hassle free operation. Available with 17" or 19" A-Grade LCD panels, combo DB15 single, 8 or 16 port integrated KVM switch & with an option remote IP console.



FEATURES:

- Support combo interface, VGA-USB & VGA-PS/2.
- Durable 104-key keyboard and touch pad.
- Quick and simple installation.
- Self-locking and auto release rails for ultra-convenience.
- Port selection via push buttons or On-Screen-Display (OSD).
- Dedicated daisy chain port to expand up to 240 servers.
- Access Control List (ACL) security function for up to 8 independent user accounts.

OPTIONAL REMOTE IP ACCESS:

- An expansion slot allows you to add an optional KVM over IP module to enable remote access to your servers.
- Gain BIOS level access to your servers for system maintenance, support or failure recovery via secure SSL authentication and encryption.



SPECIFICATIONS

Part no.	AVP117e-220DC	AVP117S8e-220DC	AVP117S16e-220DC
Direct no. of Computers	1	8	16
Maximum no. of Computers	1	232(Daisy Chain)	240(Daisy chain)
LCD	Size	17"	
	Backlight	LED	
	Resolution	1280*1024	
	Max. Color	16.7M	
	Luminance	250cd/m2	
	View Angel (H/V)	176 / 170	
	Contrast Ratio	1000 : 1	
Port Selection	N/A	Push Button, OSD or Hotkey	
Expansion Slot	N/A	Yes, option for Remote IP Access	
KB/Mouse Emulation	USB & PS2		
Rack Depth	500mm to 1100mm (rack cabinet front rails to rear rails)		
Power	220VDC Terminal Block "+" and "-".		
Environment	Operation temp: 0 to 50°C Storage temp: -20 to 60°C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration (11ms duration) Vibration: 17 to 500Hz 1G PTP		
Physical Dimensions / Net Weights	448x42x580mm (WxHxD) / 12.0KG		
Packing Dimensions / Gross weights	715x140x780mm (WxHxD) / 18.0KG		
Accessory	1.8meter IEC Type Power Cord (1.8meter VGA& PS2Cable + 1.8meter USB A Type Cable for AVP117e/119e		

Option Relate Item			
AB-6	1.8meter 2-in-1 KVM Cable-USB&VGA	AC-6	1.8meter 3-in-1 KVM Cable-PS/2&VGA
AB-10	3.0meter 2-in-1 KVM Cable-USB&VGA	AC-10	3.0meter 3-in-1 KVM Cable-PS/2&VGA
AB-15	5.0meter 2-in-1 KVM Cable-USB&VGA	AC-15	5.0meter 3-in-1 KVM Cable-PS/2&VGA
AIP101	KVM over IP module for Remote Bios Level Access		



