

BHK Series

2U DUAL-SCREEN RACK MOUNT DISPLAYS

2U Rackmount Dual 2 x 17.3" LCD integrated with 101-key pull out backlit keyboard and touchpad, VGA x 2, DVI-D x 2, S-Video x 2, Composite x 2, SDI in/Out x 2, for each display
3.5" (2U rack height) x 17.5" W x 26" D / 48 lbs

Temperature: MIL-STD- 810E (501.4, 502.4), Humidity: MIL-STD-810E (507.2)
Altitude: MIL-STD-810E (500.3), Vibration: MIL-STD-810E (514.4)
Shock: MIL-STD-810E (516.4)

MODEL: BHK2DW117e-R-SDI



SPECIFICATIONS:

Product Display	Dual 17.3" Full HD 1920 X 1080
Viewing Angle	Displays Tilt ~15° From Vertical
Ports	2x USB Pass Through Inputs On Front + 1x USB Inputs On Rear, Analog VGA, DVI-D, HD-SDI, S VIDEO-IN for each display
Power Supply	18 - 36 VDC
Keyboard & Mouse	101 Keys Backlit Keyboard with Touchpad and Adjustable Brightness. Resistive Touchpad Optional: Waterproof Keyboard
Dimensions	Height: 2u - 3.46" (88mm) Width: 17.76" (451mm) Depth: 25.89" (657.6mm)
Weight	~42 Lbs (19kg)
Temperature	Mil-STD-810e (501.4, 502.4), Operating: 0 ~ 50°C, Non-Operating: -40 ~ 70°C
Humidity	Mil-STD-810e (507.2), Relative Humidity: 5% To 95% Operating, Non-Condensing
Altitude	Mil-STD-810e (500.3), Operating: 15,000 Ft (4571.8 M), Non-Operating: 40,000 Ft (12,192 M)
Vibration	Mil-STD-810e (514.4), Operating: 10 To 500 Hz 1.04 G (Rms)
Shock	Mil-STD-810e (516.4), Operating: 15 G, 8 Ms 1/2 Sine, Non-Operating: 40 G, 8 Ms 1/2 Sine
Drop	4" Stand Alone, 39" Transit Drop In Transit Case
Regulation	CE, FCC, CCC
Warranty	1 Year Parts And Labor

