

1U Rackmount 15" TFT LCD Monitor Dual Slides Optional 8-port/16-port KVM switch



Specification

Model No	BHK1015e / 1015-8e / 1015-16e
Ports switch	D-Sub 15 pin
Power Supply	AC 110/220V Auto Switch or DC+48V
Construction	Heavy-duty steel
Keyboard	Membrane 105 keys with touchpad
Protection	Tempered glass protection to the LCD screen
Operation Temp.	0-50°C(32-122°F)
Approval	CE, FCC
Display	
Diagonal	15" (381mm)
LCD Resolution	1024 x 768
Brightness	250 nits
Viewing angle	120/120
Contrast Ratio	350:1
Backlight MTBF	50,000 hours under 20 - 30°C
Frame Rate	60Hz

Accessories	Extension Bracket	Power cord	Adjustable bracket Max. Length	KVM Cable
BHK1015e	x 1 pair	x 1	22.5"-35.5"	x 1
BHK1015-8e	x 1 pair	x 1	22.5"-35.5"	x 8
BHK1015-16e	x 1 pair	x 1	22.5"-35.5"	x 16

Order Information

Weight (Net / Gross weight)	
BHK1015e	25.3 lbs / 37.4lbs (11.5 kg/17 kg)
BHK1015-8e	28.6 lbs / 39.6 lbs (13 kg/18 kg)
BHK1015-16e	28.6 lbs / 48.2 lbs (13 kg/22 kg)
Dimensions	
BHK1015e	442.4(17.4")W x 44.5 (1.75")H x 480(21.7")D
BHK1015-8e	442.4(17.4")W x 44.5 (1.75")H x 590(24.6")D
BHK1015-16e	442.4(17.4")W x 44.5 (1.75")H x 590(24.6")D

Model: BHK1015e, BHK1015-8e, and BHK1015-16e

Features:

- Only 1U (1.75" high) of vertical 19" rack-mount space.
- Meets EIA310c & IEC-3 Specifications
- Full 101-keys Windows keyboard
- Support DOS, Windows OS, Netware, SCO Unix, HP Unix, Linux
- Anti-Glare Tempered Glass for added protection
- Auto LCD turned off when LCD screen is turned down position.
- Built-in Rail Self-locking device
- Standard keyboard, mouse and VGA Cable
- Built-in power adapter
- Keyboard with GlidePoint touch pad mouse
- Built-in on screen display controlled by integral membrane switches

With KVM Option only:

- **Multi-platform-mix** PCs, SUNs, IBMs, HPs, Compaq & DELL
- **Support 8 characters password protection** & search PC server name
- **Cascades for use with up to 128 servers**
- New keep alive feature safeguards server for power loss to the switch
- **Built-in microprocessor** emulation for each port boots up process
- **Auto scan-mode** for monitoring your servers at intervals 5 to 99s
- **Hot-plug** when adding or removing PC w/o powering down the switch
- Name your server up to **16 characters long**

BHK1015e



BHK1015-8e



BHK1015-16e

