

# 1U Rackmount 17" TFT LCD Monitor USB Keyboard Mouse Optional 8-port/16-port KVM switch



## Specification

<b>Model No</b>	<b>BHK117ue / 117-8ue / 117-16ue</b>
Ports switch	D-Sub 15 pin
Weight	16kgs
Dimension	442.4 x 44.5 x 550mm (WxHxD)
Power Supply	AC 110/220V Auto Switch or DC+48V
Construction	Heavy-duty steel
Keyboard	Membrane 105 keys with touchpad
Protection	Tempered glass protection to the LCD screen
Operation Temp.	0-50°C(32-122°F)
Approval	CE, FCC
<b>Display</b>	
Diagonal	17" (431.8mm)
LCD Resolution	1280 x 1024
Brightness	300 nits
Viewing angle	160/160
Contrast Ratio	450:1
Backlight MTBF	50,000 hours under 20 - 30°C
Frame Rate	60Hz

Accessories	Extension Bracket	Power cord	Adjustable bracket Max. Length	KVM Cable
BHK117ue	x 1 pair	x 1	22.5"-35.5"	x 1
BHK117-8ue	x 1 pair	x 1	25"-37"	x 8
BHK117-16ue	x 1 pair	x 1	24.5"-37.5"	x 16

## Order Information

Weight (Net / Gross weight)	
BHK117ue	33.0 lbs / 44.0lbs (15 kg/20 kg)
BHK117-8ue	35.2 lbs / 46.2 lbs (16 kg/21 kg)
BHK117-16ue	37.4 lbs / 48.2 lbs (17 kg/22 kg)
Dimensions	
BHK117ue	442.4(17.4")W x 44.5 (1.75")H x 550(21.7")D
BHK117-8ue	442.4(17.4")W x 44.5 (1.75")H x 625(24.6")D
BHK117-16ue	442.4(17.4")W x 44.5 (1.75")H x 625(24.6")D

**Model: BHK117ue, BHK117-8ue, and BHK117-16ue**

### Features:

- Only 1U (1.75" high) of vertical 19" rack-mount space.
- Meets EIA310c & IEC-3 Specifications
- Full 101-keys Windows keyboard
- Support DOS, Windows OS, Netware, SCO Unix, HP Unix, Linux
- Anti-Glare Tempered Glass for added protection
- Auto LCD turned off when LCD screen is turned down position.
- Built-in Rail Self-locking device
- Standard keyboard, mouse and VGA Cable
- Built-in power adapter
- Keyboard with GlidePoint touch pad mouse
- Built-in on screen display controlled by integral membrane switches

### With KVM Option only:

- **Multi-platform-mix** PCs, SUNs, IBMs, HPs, Compaq & DELL
- **Support 8 characters password protection** & search PC server name
- **Cascades for use with up to 128 servers**
- New keep alive feature safeguards server for power loss to the switch
- **Built-in microprocessor** emulation for each port boots up process
- **Auto scan-mode** for monitoring your servers at intervals 5 to 99s
- **Hot-plug** when adding or removing PC w/o powering down the switch
- Name your server up to **16 characters long**

**BHK117ue**



**BHK117-8ue**



**BHK117-16ue**

