

1U Rackmount 17" TFT LCD Monitor Wide Screen (16:9) Optional 8-port/16-port KVM switch



Specification

Model No	BHK117we / 117-8we / 117-16we
Ports switch	D-Sub 15 pin
Weight	11kgs/11.5kgs/11.5kgs
Dimension	442.4 x 44 x 508mm (WxHxD)
Power Supply	AC 110/220V Auto Switch or DC+48V
Construction	Heavy-duty steel
Keyboard	Membrane 105 keys with touchpad
Protection	Tempered glass protection to the LCD screen
Operation Temp.	0-50°C(32-122°F)
Approval	CE, FCC
Display	
Diagonal	17" (431.8mm)
LCD Resolution	1280 x 768
Brightness	450 nits
Viewing angle	160/160
Contrast Ratio	600:1
Backlight MTBF	50,000 hours under 20 - 30°C
Frame Rate	60Hz

Accessories	Extension Bracket	Power cord	Adjustable bracket Max. Length	KVM Cable
BHK117we	X 1 pair	x 1	22.5"-35.5"	x 1
BHK117-8we	X 1 pair	x 1	25"-37"	x 8
BHK117-16we	X 1 pair	x 1	24.5"-37.5"	x 16

Order Information

Weight (Net / Gross weight)	
BHK117we	24.2 lbs / 44.0lbs (11 kg/20 kg)
BHK117-8we	25.3 lbs / 46.2 lbs (11.5 kg/21 kg)
BHK117-16we	25.3 lbs / 48.2 lbs (11.5 kg/22 kg)
Dimensions	
BHK117we	442.4(17.4")W x 44 (1.75")H x 508(19.98")D
BHK117-8we	442.4(17.4")W x 44 (1.75")H x 508(19.98")D
BHK117-16we	442.4(17.4")W x 44 (1.75")H x 508(19.98")D

Model: BHK117we, BHK117-8we, and BHK117-16we Features:

- Only 1U (1.75" high) of vertical 19" rack-mount space.
- Meets EIA310c & IEC-3 Specifications
- Full 105-keys Windows keyboard
- Support DOS, Windows OS, Netware, SCO Unix, HP Unix, Linux
- Anti-Glare Tempered Glass for added protection
- Auto LCD turned off when LCD screen is turned down position.
- Built-in Rail Self-locking device
- Standard keyboard, mouse and VGA Cable
- Built-in power adapter
- Keyboard with GlidePoint touch pad mouse
- Built-in on screen display controlled by integral membrane switches

With KVM Option only:

- **Multi-platform**-mix PCs, SUNs, IBMs, HPs, Compaq & DELL
- **Support 8 characters password protection** & search PC server name
- **Cascades for use with up to 128 servers**
- New keep alive feature safeguards server for power loss to the switch
- **Built-in microprocessor** emulation for each port boots up process
- **Auto scan-mode** for monitoring your servers at intervals 5 to 99s
- **Hot-plug** when adding or removing PC w/o powering down the switch
- Name your server up to **16 characters long**

BHK117we



BHK117-8we



BHK117-16we

