

Industrial KEYBOARD

Bluetooth®-Compatible, Wireless Industrial Keyboard with Touchpad

Model: BT-87-TP-IS



The first Bluetooth®-compatible, wireless industrial keyboard with an integrated touchpad - the BT-87-TP-IS. This fully-sealed keyboard is designed to meet NEMA 4X specifications, meaning it is resistant to dirt, dust, water, ice and corrosives. Built with an industrial silicone rubber keypad and a rugged ABS polycarbonate case, the BT-87-TP-IS is submersible and easy to clean with disinfectants. The compact design and internal Bluetooth® module make the BT-87-TP-IS highly portable. It is an ideal fit for mobile, material handling, food and beverage processing, medical, and other environments where rugged flexibility is a necessity. The BT-87-TP-IS requires 2 AA batteries for power and does not require a USB dongle if your computer has an internal Bluetooth® radio. Features: 12 Function Keys Built-In Mounting Holes Class 2 Output Power Integrated Touchpad Up to a 30-foot Range Bluetooth®- compatible version 2.0

FEATURES:



- 12-Key Numeric Pad
- Built-In Mounting Holes
- Class 2 Output Power
- Integrated Touchpad
- Up to a 30-foot Range
- Bluetooth®- compatible version 2.0

SPECIFICATIONS:

CERTIFICATIONS	IP68
SHOCK	3 X 11 ms pulses of 50g on each of 3 axes
KEY SWITCH	MATERIAL: Industrial Silicone Rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.03 oz +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
POWER	2 AA Batteries
COMPATIBILITY	All Windows Operating Systems
TEMPERATURE RANGE	STORAGE: -40C to +65C (-40F to +149F) OPERATING: 0C to +60C (+32F to +140F)
WEIGHT	2.00 lbs +/- 0.10 lbs (0.91 kg +/- 0.05 kg)
WARRANTY	1 Year Limited Warranty
HUMIDITY	100%
DIMENSIONS	12.01" x 7.75" x 2.03" (w-h-d) 305.54 mm x 196.85 mm x 51.56 mm



MECHANICAL DRAWING



KEY SWITCH

MATERIAL: Industrial Silicone Rubber
 LIFE: Greater Than 10 Million Cycles
 TRAVEL: 0.055 in.
 ACTUATION FORCE: 7.03 oz. +/- 1.06oz (200g +/- 30g)
 FEEDBACK: Tactile with Mechanical Snap

TEMPERATURE RANGE

STORAGE: -40°F to +149°F (-40°C to +65°C)
 OPERATING: 32°F to +140°F (0°C to +60°C)

VIBRATION

POWER SPECTRAL DENSITY: .04g/HZ
 FREQUENCY RANGE: 20Hz-2Khz
 DURATION OF TEST PER AXIS: 3 hours

POWER

BLUETOOTH: 2 AA Batteries

HUMIDITY

100% Humidity Resistant


SHOCK

3 X 11 ms pulses of 50g on each of 3 axis

WEIGHT

2.00 lbs +/- 0.10 lbs (0.91 kg +/- 0.05 kg)

BACK/MOUNTING



ENCLOSURE CASE: ABS/Polycarbonate

