

# Full HD Multi Touch-Monitor

Digital signage IP65 front/IP54 all sides, Semi-outdoor  
42" 1920 x 1080, 500 Nits, 3000:1, 178/178, Video Input DVI x  
1, Ear Phone Jack x 1, Built In speakers 8W\*2 with Tempered  
Glass. AC Power input 110/220V Input Optional VGA or HDMI  
Input, IR or PCT touch, AR/AG glass

Model: BU4200L



## FEATURES:

- Full HD LED display.
- IR multi-touch 6 touch points or 2-points Projective Capacitive Touch (1-2mm) USB Controller
- USB touch controller, DVI, VGA and built-in speakers
- Easy for wall mount use

## SPECIFICATONS

|                          |                       |
|--------------------------|-----------------------|
| Integrated Touch System  | IR/PCT                |
| Touch Points             | 10                    |
| <b>LED Panel SIZE</b>    | 42"                   |
| AUO P-Grade Panel Model  | P42HVNXX              |
| Native Res.              | 1920 x 1080           |
| Brightness               | 500 cd/m2             |
| Contrast Ratio           | 3000:1                |
| View Angle               | 178 / 178             |
| <b>LCD Control Board</b> | Long life             |
| Input Video              | DVI x 1               |
| Analog Video             | VGA or HDMI option    |
| Audio                    | Ear Phone Jack x 1    |
| USB Touch                | USB Touch x 1         |
| <b>SPEAKERS</b>          | 8W*2                  |
| <b>CABINET - IP-XY</b>   | IP-54 -- 65           |
| Dimension                | 799x493x84            |
| <b>Special Features</b>  | PCT or IR touch       |
| Option                   | With AG/AR glass      |
| base on order            | Portrait or Landscape |
| PC Feature - i5 serial   | i5/500GB-HDD/4G ddr-3 |
| J1900 serial             | J1900/500GB-HDD/DDR-3 |

# MECHANICAL DRAWING:

