



Model: FCH1700

17" Black Desktop LCD Monitor (FOB NJ)

Features

- * "Designed for touch" stable photo stand
- * Standard VGA(DB-15) analog Plug-and-Play
- * Superior viewing angles, contrast ratio, and brightness
- * Built-in two 1.5W speakers with amplifier
- * User friendly OSD controls
- * Worldwide agency approvals



Specifications:

| | | |
|----------------------------|---|---|
| LCD panel | TFT Active Matrix color 17 in (432 mm) diagonal viewable SXGA 1280 x 1024 resolution (maximum) 0.264 x 0.264 mm pixel pitch 16 million displayable colors 250 nit brightness (typical) | 80% brightness uniformity (minimum) 400:1 contrast ratio (typical) 25 ms response time (typical at 25oC) 170o (H), 170o (V) viewing angle (minimum) 50,000 hours MTBF (minimum at 25oC) |
| On-Screen Display (OSD) | Brightness, Contrast, Phase, Clock, Volume, H&V Position, Auto-tune, Recall | |
| Video Interface | RGB analog D-sub 15 pin 24-62 kHz horizontal scan 50-75 Hz vertical refresh | |
| Regulatory | Safety: UL/CUL, TUV-GS, CB EMI: FCC(DOC), VCCI, CE Ergonomics: TCO99 (optional) | |
| Power Management | meet VESA DPMS & Energy Star requirements 5W sleep mode, 30W normal mode IEC 320/EN 60320 Power Inlet | |
| Mechanical and Environment | Operation temperature: 0~50oC [32~122oF] Storage temperature: -20~65oC [-4~149oF] Humidity:10- 85% (operating), 10-90% (storage) Altitude: 0-10,000 ft (operating), 0-40,000 ft (storage) 393.7 x 330.2 x 69.85 mm[15.5 x 13 x 2.75 inch] 15 lbs/ 6.8 kg | |
| Others | 75 x 75 mm VESA mounting holes 1.5W speaker x 2 with amplifier | |

Options

- * Durable touch screen
- * CM-330 VGA-to-Video adapter
- * AMS-0011 Media Station

