



Model: FOP1900

# 19" Open Frame LCD Monitor

## Features

- \* RoHS compliant, meet UL, CSA, TUV, FCC B, VCCI B, CE, TCO 99, TUV Ergo, EPA Energy Star certification
- \* Kiosks, equipment, and instruments drop-in design
- \* Friendly design on various location options of OSD keys
- \* Superior viewing angles, contrast ratio, and brightness
- \* Sturdy and ventilation consideration structure





## Specifications:

<b>LCD panel</b>	TFT Active Matrix color	80% brightness uniformity (typical)
	19 in/ 482.6 mm diagonal viewable	500:1 contrast ratio (typical)
<b>Video Interface</b>	SXGA 1280 x 1024 resolution (maximum)	10 ms response time (typical at 25oC)
	0.294 x 0.294 mm pixel pitch	150o (H), 130o (V) viewing angle (typical at CR=10)
	16 million displayable colors	50,000 hours MTBF (typical at 25oC)
	250 nit brightness (typical, 80% touch option)	
<b>Power Management</b>	VGA compatible analog RGB	
	24-80 kHz horizontal scan	
	50-75 Hz vertical refresh	
	On-screen display	
<b>Mechanical and Environment</b>	VESA DPMS standard	
	5W sleep mode, 45W normal mode	
	12 V/4.16 A, 50 W, Universal Input Adapter	
<b>Mechanical and Environment</b>	Operation temperature: 0~50oC [32~122oF]	
	Storage temperature: -20~60oC [-4~140oF]	
	Humidity: 85% (maximum)	
	455 x 351 x 49.8 mm [17.9 x 13.8 x 1.96 inch]	
	6 Kg [13.2 Lb]	

## Options

- \* Durable Resistive, and Surface Acoustic Wave touchscreen
- \* DVI, Composite Video, BNC video output
- \* Embedded Stand-Alone or Network MPEG Players





Model: FOP1900

# 19" Open Frame LCD Monitor

