

FULL IP65 STAINLESS LCD MONITOR

High Brightness Rugged Completely Sealed Full IP66/NEMA4X Stainless Steel Chassis/Surface Mount, 19" Brightness 1000 nits with PCAP Touchscreen USB controller, 1280x1024 based on Default 3 set waterproof connectors Waterproof connectors & cables: DVI,VG, USB & Power 6ft long only with external 100~240V AC + adapter Wide Temp -30 to 50C Operating Temp.




MODEL: CCH1900HB-SIP-PCT

FEATURES:

- High Contrast color TFT LCD Monitor support resolution up to SXGA(1280 x 1024)
- Widely used in chemical industry, food industry, medical devices, appliances etc. with good corrosion resistance



Standard VGA DVI + Power input



USB for touchscreen (Optional)



(Standard 6ft long), option for 10ft or 15ft



OSD



Standard external Power adapter, standard I/O Water proof cable: 1 x VGA, Power x1 6ft long

OPTIONAL:



All in one PC with touch Included IP water proof connectors and cables



Power, USB, COM, VGA, LAN and Audio out



For outdoor used integrated with pressure release valve.



Optional for front Light Sensor for High brightness LCD

SPECIFICATIONS:

Display	Viewing Size Image	19"
	Active Display Area (mm)	378(H) x 303 (V)
	Pixel Pitch (mm)	0.294 (H) x 0.294(V)
	Resolution	1280 x 1024
	Contrast Ratio	2000 : 1 (typ.)
	Color	16.7M (8bits/colors)
	Brightness	1000 cd/m ²
	Viewing Angle	-89~89 (H) ; -89~89(V)
	Recommended Resolution	1280 x 1024 @ 60Hz, 75 Hz
	Signal Connector	VGA,DVI, USB
Power	Source	12V DC in,with External AC-DC Adapter(100-240V)
	Consumption	51W typical, normal operation
	Management	VESA DPMS Compliant
Optional	Touch	Resistive, PCAP
	High Brightness	1000,1500
	Auto Dimming	YES
	POWER in	DC24V,DC 9V~36V
	Remote Control	YES
	IO	AV,HDMI,DP



*Specifications subject to change without notice, not responsible for typographical errors.

DRAWINGS FOR REFERENCE:

This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.

