

# Full IP65 Stainless LCD Monitor

Rugged Completely Sealed Full IP66/NEMA4X Stainless Steel Chassis/Surface Mount, 21.5" LCD monitor, 1920 x 1080, 1000 nits, with Glass, VGA and DVI input.

## MODEL: CCH2150HB-SIP



USB INPUT IS OPTIONAL  
FOR TOUCHSCREEN

### Features:

- High Contrast color TFT LCD Monitor support resolution up to Full HD (1920 x 1080 )
- Widely used in chemical industry, food industry, medical devices, appliances etc. with good corrosion resistance

### Specifications:

<b>Display</b>	Viewing Size Image	21.5"
	Active Display Area (mm)	476.64 (H) x 268.11 (V)
	Pixel Pitch (mm)	0.248 x 0.248
	Resolution	1920 x 1080
	Contrast Ratio	5000 : 1 (typ.)
	Color	16.7M
	Brightness	1000 cd/m <sup>2</sup>
	Viewing Angle	-89~89 (H) ; -89~89(V)
	Recommended Resolution	1920 x 1080 @ 60Hz
	Signal Connector	VGA,DVI
<b>Power</b>	Source	12V DC in,with External AC-DC Adapter(100-240V)
	Consumption	38W typical, normal operation
	Management	VESA DPMS Compliant
<b>Optional</b>	Touch	Resistive, PCAP
	High Brightness	1000,1500
	Auto Dimming	YES
	POWER in	DC24V,DC 9V~36V
	Remote Control	YES
	IO	AV,HDMI,DP

### IP65 Waterproof connectors:



VGA Input DVI Input USB Input Power Input  
(Option)

# Mechanical Drawing

