

Full IP65 Stainless LCD Monitor

Rugged Completely Sealed Full IP66/NEMA4X

Stainless Steel Chassis/Surface Mount, 24" Normal Brightness 300 nits, 1920x1080 with external 100~240V AC + adapters based on Default 3 set waterproof connectors Waterproof connectors & cables: DVI,VGA & Power 6ft long only

Model: CCHW2400-SIP

**USB INPUT IS OPTIONAL
FOR TOUCHSCREEN**

FEATURES:

- High Contrast color TFT LCD Monitor support resolution up to Full HD (1920 x 1080)
- Widely used in chemical industry, food industry, medical devices, appliances etc. with good corrosion resistance

SPECIFICATIONS:

Display	Viewing Size Image	24"
	Active Display Area (mm)	531.36 (H) x 298.89 (V)
	Pixel Pitch (mm)	0.27675 (H) x 0.27675(V)
	Resolution	1920 x 1080
	Contrast Ratio	3000: 1 (typ.)
	Color	16.7M(8bits+color)
	Brightness	300 cd/m ²
	Viewing Angle	-89~89 (H) ; -89~89 (V)
	Recommended Resolution	1920 x 1080 @ 60Hz
	Signal Connector	VGA,DVI, USB for Touch
Power	Source	12V DC in, with External AC-DC Adapter(100-240V)
	Consumption	45W typical, normal operation
	Management	VESA DPMS Compliant
Optional	Touch	Resistive, PCAP ,IR
	High Brightness	YES
	Auto Dimming	YES
	POWER in	DC24V,DC9V~36V
	Remote Control	YES
	IO	AV,HDMI,DP

IP65 Waterproof connectors:



VGA Input DVI Input USB Input Power Input
(Option)

MECHANICAL DRAWING:

