

INDUSTRIAL CHASSIS/WALL MOUNT HEAVY DUTY METAL



Front Water and dust Proof IP65/NEMA 4 w/ IP65 Solid Back housing except I/O. 24" LCD monitor, 1920x1080, 250nits VGA + DVI Input, Side OSD, with protective front glass+12 VDC External power supply 100-240 VAC 50-60Hz included.

Operating Temp & Storage Temp Support: -20~70°C

Model: CCHW2400WTIP

Rugged IP65/NEMA4X Industrial touch screen monitor, iTech is the perfect solution for Dusty and Wet industrial environments. Heavy duty Metal housing with powder coating and affordable.

FEATURES:

- High Contrast color TFT LCD Monitor support resolution up to FULL HD (1920 x 1080)
- Power management system conforms to VESA DPMS and EPA Energy Star standards.
- Full consideration for touch screen installation and application.
- Universal Power adapter.
- Support DDC1 & DDC2B for Plug & Play compatibility.
- Advanced OSD control for picture quality adjustment.
- Detachable stand for wall-mounting application.
- Heavy duty Monitor with steel frame.
- Front IP65/NEMA4 Optional with PCAP or 5 Wire Resistive Touch Screen Options
- IP65 Solid Back housing except I/O and VESA mounting
- Custom design by request.

SPECIFICATIONS:

| | | |
|-----------------|--------------------------|---|
| Display | Viewing Size Image | 24" |
| | Active Display Area (mm) | 531.36 (H) x 298.89 (V) |
| | Pixel Pitch (mm) | 0.27675 (H) x 0.27675(V) |
| | Resolution | 1920 x 1080 |
| | Contrast Ratio | 3000: 1 (typ.) |
| | Color | 16.7M(8bits+color) |
| | Brightness | 250 cd/m ² |
| | Viewing Angle | -89~89 (H) ; -89~89 (V) |
| | Recommended Resolution | 1920 x 1080 @ 60Hz |
| | Signal Connector | VGA,DVI |
| Power | Source | 12V DC in, with External AC-DC Adapter(100-240V) |
| | Consumption | 45W typical, normal operation |
| | Management | VESA DPMS Compliant |
| Optional | Touch | Resistive, PCAP ,IR |
| | High Brightness | YES |
| | Auto Dimming | YES |
| | POWER in | DC24V,DC9V~36V |
| | Remote Control | YES |
| | IO | Video: |
| Power: | | 12 VDC External power supply 100-240 VAC 50-60Hz included |

