

Full IP65 Stainless LCD Monitor

Rugged Completely Sealed Full IP66/NEMA4X Stainless Steel Chassis/Surface Mount, 55" LCD monitor, 1920 x 1080, 450 nits, with Glass, VGA and DVI input with Projective Capacitive Touch (1-2mm) USB Controller

MODEL: CCHW5500-SIP-PCT



USB INPUT IS OPTIONAL
FOR TOUCHSCREEN

Features:

- High contrast color TFT LCD monitor support resolution up to Full HD (1920x1080)
- Widely used in chemical industry, food industry, medical devices, appliances etc with good corrosion resistance.

Specifications:

Display	Viewing Size Image	55"
	Active Display Area (mm)	1209.6 (H) x 680.4 (V)
	Pixel Pitch (mm)	0.21(H)x 0.63(V)
	Resolution	1920x1080
	Contrast Ratio	4000 : 1 (typ.)
	Color	1073.7M (10bits/color)
	Brightness	450 cd/m ²
	Viewing Angle	-89~89 (H) ; -89~89(V)
	Recommended Resolution	1920 x 1080 @ 60Hz
	Signal Connector	VGA,DVI
Power	Source	AC100V~AC240V
	Consumption	170W typical, normal operation
	Management	VESA DPMS Compliant
Optional	Touch	Resistive, PCAP,IR
	High Brightness	1000,1500
	Auto Dimming	YES
	POWER in	DC24V
	Remote Control	YES
	IO	AV,HDMI,DP

IP65 Waterproof connectors:



VGA Input DVI Input USB Input Power Input
(Option)

Mechanical Drawing

