

RUGGED COMPLETELY SEALED FULL IP66/NEMA4X STAINLESS STEEL

Chassis/Surface Mount, 65" Normal Brightness 200-300 nits with external
100~240V AC + adapters based on Default 3 set waterproof connectors
Waterproof connectors & cables: DVI,VGA & Power 6ft long only

MODEL: CCHW6500-SIP



Rugged IP65/NEMA4X Industrial touch screen monitor, iTech is the perfect solution for Dusty and Wet industrial environments. Heavy duty Metal housing with powder coating and affordable.

FEATURES:

- High Contrast color TFT LCD Monitor support resolution up to FULL HD (1920 x 1080)
- Power management system conforms to VESA DPMS and EPA Energy Star standards.
- Full consideration for touch screen installation and application.
- Universal Power adapter.
- Support DDC1 & DDC2B for Plug & Play compatibility.
- Advanced OSD control for picture quality adjustment.
- Detachable stand for wall-mounting application.
- Heavy duty Monitor with steel frame.
- Front IP64/NEMA4X Optional with PCAP or 5 Wire Resistive Touch Screen Options
- IP66 Solid Back housing except I/O and VESA mounting
- Custom design by request.

SPECIFICATIONS:

Display	Viewing Size Image	65"
	Active Display Area (mm)	1432 (H) x 807 (V)
	Pixel Pitch (mm)	0.744(H)x 0.744(V)
	Resolution	1920 x 1080
	Contrast Ratio	5000:1 (typ.)
	Color	1073.7M (10bits/color)
	Viewing Angle	-89~89 (H) ; -89~89 (V)
	Brightness	300 cd/m2
	Recommended Resolution	1920 x 1080 @ 60Hz 10bit 1.07B
Signal Connector	VGA,DVI	
Power	Source	AC100V~AC240V
	Consumption	248W typical, normal operation
	Management	VESA DPMS Compliant
Optional	Touch	Resistive, PCAP ,IR
	High Brightness	1000,1500
	Auto Dimming	YES
	POWER in	24V, 9~36V
	Remote Control	YES
	IO	Video:
Power:		12 VDC External power supply 100-240 VAC 50-60Hz included

MECHANICAL DRAWING

