

# Full IP65 Stainless LCD Monitor

Rugged Completely Sealed Full IP66/NEMA4X Stainless Steel Chassis/Surface Mount, 19" LCD monitor, 1280 x 1024, 1000 nits, with Glass, VGA and DVI input.

**MODEL: CCH1900HB-SIP**



**USB INPUT IS OPTIONAL  
FOR TOUCHSCREEN**

## FEATURES:

- High Contrast color TFT LCD Monitor support resolution up to SXGA(1280 x 1024 )
- Widely used in chemical industry, food industry, medical devices, appliances etc. with good corrosion resistance

## SPECIFICATIONS:

<b>Display</b>	Viewing Size Image	19"
	Active Display Area (mm)	378(H) x 303 (V)
	Pixel Pitch (mm)	0.294 (H) x 0.294(V)
	Resolution	1280 x 1024
	Contrast Ratio	2000 : 1 (typ.)
	Color	16.7M (8bits/colors)
	Brightness	1000 cd/m <sup>2</sup>
	Viewing Angle	-89~89 (H) ; -89~89(V)
	Recommended Resolution	1280 x 1024 @ 60Hz, 75 Hz
	Signal Connector	VGA,DVI
<b>Power</b>	Source	12V DC in,with External AC-DC Adapter(100-240V)
	Consumption	51W typical, normal operation
	Management	VESA DPMS Compliant
<b>Optional</b>	Touch	Resistive, PCAP
	High Brightness	1000,1500
	Auto Dimming	YES
	POWER in	DC24V,DC 9V~36V
	Remote Control	YES
	IO	AV,HDMI,DP

### IP65 Waterproof connectors:



VGA Input DVI Input USB Input Power Input  
(Option)

*\*Specifications subject to change without notice, not responsible for typographical errors.*

**MECHANICAL DRAWING:**

*This is subject to change without Notice. Final Drawings Will be Provided for Approval after Order.*

