

RUGGED COMPLETELY SEALED FULL IP66/NEMA4X STAINLESS STEEL



Chassis/Surface Mount, 17.3" Normal Brightness 250 nits, 1920x1080 with Projective Capacitive Touch (1-2mm) USB Controller
 Default 3 set waterproof connectors Waterproof connectors & cables: DVI,VGA USB for touchscreen & Power 6ft long only with 12V DC input

MODEL: CCHW1730-SIP-PCAP

FEATURES:

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Available with auto-brightness sensor offers application in day and night
- Stainless Steel Enclosure
- Complete custom design/solution for OEM customers

SPECIFICATIONS:

Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	Wide / 17.3" viewable diagonal area
	Active Area / Pixel Pitch	381.888(H) x 214.812(V) mm / 0.1989(H) x 0.1989(V) mm
	Native Resolution / Colors	1920(H) x 1080(V) / 262 K
	Brightness / Contrast	250 cd/m ² (typ) / 400 : 1
	Response Time	< 8 ms
	Viewing Angle (typical)	H.90° (- 45° ~ + 45°) , V. 50° (- 30° ~ + 20°)
	Light Source	LED backlight, Long life, 35,000 hrs (typ)
Input Sources	DVI + VGA (No Speakers)	
Convenient Features	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)	
	OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)	
Power	12V DC in	
Power Consumption	Operation / Power Saving	15 watt , < 1 watt (Support DPMS)
Operating Condition	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)
Storage Condition	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)
Certification		FCC , CE
Dimensions	Physical	Please refer to Drawing
	Carton	W x H x D = TBD
Weight	N.W. / G.W.	4.5 Kgs / 5.5 Kgs
Container Loaded	20ft / 40ft / 40ft HQ	TBD (Sets , By pallet)

Options	Touch	Video / TV	Enhanced Panel	Others
	Resistive touch	SV + AV	Panel with LED backlight	Digital Signage(Stand alone)
	Capacitive touch	SV + AV + AV_Looping	High brightness panel	Networking Digital Signage
	Infrared touch	SV + AV + TV	Wide Temperature	Motion Sensor
	Protected glass		Sunlight Readable	Light Sensor
				Auto-Dimming

MECHANICAL DRAWING

