



17.3" Normal Brightness 1000 nits, 1920x1080 with Projective Capacitive Touch (1-2mm) USB Controller, Default 3 set waterproof connectors Waterproof connectors & cables: DVI+HDMI+ USB for touchscreen & Power 15ft long only with 100-240VAC US Power cord.

**MODEL: CCHW1730HB-SIP-PCAP**

**FEATURES:**

- Modularize mechanical design provides flexible product configuration and easy maintenance
- Optional build-in touch screen for interactive application
- Available with auto-brightness sensor offers application in day and night
- Stainless Steel Enclosure
- Complete custom design/solution for OEM customers

**SPECIFICATIONS:**

<b>Panel</b>	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating
	Aspect Ratio / Size	Wide / 17.3" viewable diagonal area
	Active Area / Pixel Pitch	381.888(H) x 214.812(V) mm / 0.1989(H) x 0.1989(V) mm
	Native Resolution / Colors	1920(H) x 1080(V) / 262 K
	Brightness / Contrast	1000 cd/m <sup>2</sup> (typ) / 400 : 1
	Response Time	< 8 ms
	Viewing Angle (typical)	H.90° (- 45° ~ + 45°) , V. 50° (- 30° ~ + 20°)
	Light Source	LED backlight, Long life, 35,000 hrs (typ)
<b>Input Sources</b>	DVI + HDMI (No Speakers)	
<b>Convenient Features</b>	Auto Calibration , Back Light Adjustment , Plug&Play (VESA DDC/CI, DDC 2B)	
	OSD Multi-Languages , Wall Mount Ready (VESA Dimension - please refer to Drawing)	
<b>Power</b>	12V DC in	
<b>Power Consumption</b>	Operation / Power Saving	15 watt , < 1 watt (Support DPMS)
<b>Operating Condition</b>	Temperature / Humidity	0°C ~ 50°C (32°F ~ 122°F) , 10% ~ 90% (no condensation)
<b>Storage Condition</b>	Temperature / Humidity	- 20°C ~ 60°C (- 4°F ~ 140°F) , 10% ~ 90% (no condensation)
<b>Certification</b>		FCC , CE
<b>Dimensions</b>	Physical	Please refer to Drawing
	Carton	W x H x D = TBD
<b>Weight</b>	N.W. / G.W.	4.5 Kgs / 5.5 Kgs
<b>Container Loaded</b>	20ft / 40ft / 40ft HQ	TBD (Sets , By pallet)

<b>Options</b>	Touch	Video / TV	Enhanced Panel	Others
	Resistive touch	SV + AV	Panel with LED backlight	Digital Signage(Stand alone)
	Capacitive touch	SV + AV + AV_Looping	High brightness panel	Networking Digital Signage
	Infrared touch	SV + AV + TV	Wide Temperature	Motion Sensor
	Protected glass		Sunlight Readable	Light Sensor
				Auto-Dimming

# MECHANICAL DRAWING

