



**21.5" High Brightness 1000nits, 1920x1080 with 10 points Projective Capacitive Touch (1-2mm) USB Controller, Default 3 set waterproof connectors Waterproof connectors & cables: DVI+HDMI+ USB for touchscreen & Power 15ft long only with 100-240VAC US Power cord.**

**Model: CCHW2150HB-SIP-PCAP**

**FEATURES:**

- High Contrast color LCD Monitor with resolution up to Full HD (1920 x 1080 )
- Completely Sealed FULL IP66/NEMA4X
- High Shock & Vibration Resistance
- Widely Application: Automation, Medical, Tourist, Transportation


**SPECIFICATIONS:**

<b>Display</b>	Viewing Size Image	21.5"
	Active Display Area (mm)	479 (H) x 270.50 (V)
	Pixel Pitch (mm)	0.248 x 0.248
	Resolution	1920 x 1080
	Contrast Ratio	5000 : 1 (typ.)
	Color	16.7M (8bits/colors)
	Brightness	1000 cd/m <sup>2</sup>
	Viewing Angle	-89~89 (H) ; -89~89 (V)
	Recommended Resolution	1920 x 1080 @ 60Hz
	Signal Connector	DVI+ HDMI
<b>Power</b>	Source	12V DC in, with External AC-DC Adapter(100-240V)
	Consumption	38W typical, normal operation
	Management	VESA DPMS Compliant
<b>Optional</b>	Touch	Resistive, PCAP
	High Brightness	YES
	Auto Dimming	YES
	POWER in	DC24V ,DC9V~36V
	Remote Control	YES
	IO	AV,HDMI,DP

**APPLICATIONS:**



## MECHANICAL DRAWING:



IP65 Waterproof connectors:



VGA Input DVI Input USB Input Power Input  
(Option)