

Front Water and dust Proof IP65/NEMA 4 with IP65 Solid Back housing except I/O 32" Wide LCD Monitor, 1920x1080, 350nits VGA + DVI Input Rear OSD, VESA Mounting12 VDC External power supply 100-240 VAC 50-60Hz included

Model: CCHW3200IP

Rugged IP65/NEMA4X Industrial touch screen monitor, iTech is the perfect solution for Dusty and Wet industrial environments. Heavy duty Metal housing with powder coating and affordable.

FEATURES:

- High Contrast color TFT LCD Monitor support resolution up to FULL HD (1920 x 1080)
- Power management system conforms to VESA DPMS and EPA Energy Star standards.
- Full consideration for touch screen installation and application.
- Universal Power adapter.
- Support DDC1 & DDC2B for Plug & Play compatibility.
- Advanced OSD control for picture quality adjustment.
- Detachable stand for wall-mounting application.
- · Heavy duty Monitor with steel frame.
- Front IP64/NEMA4X Optional with PCAP or 5 Wire Resistive Touch Screen Options
- IP65 Solid Back housing except I/O and VESA mounting
- · Custom design by request.

SPECIFICATIONS:


Display	Viewing Size Image	32"
	Active Display Area (mm)	698.4 (H) x 392.85 (V)
	Pixel Pitch (mm)	0.3638(H)x 0.3638(V)
	Resolution	1920 x 1080
	Contrast Ratio	3000: 1 (typ.)
	Color	16.7M(8bits+color)
	Viewing Angle	-89~89 (H) ; -89~89 (V)
	Brightness	350 cd/m2
	Recommended Resolution	1920 x 1080 @ 60Hz
	Signal Connector	VGA,DVI
Power	Source	AC100V~AC240V
	Consumption	75W typical, normal operation
	Management	VESA DPMS Compliant
Optional	Touch	Resistive, PCAP ,IR
	High Brightness	1000,1500
	Auto Dimming	YES
	POWER in	DC24V
	Remote Control	YES
	Ю	Video: VGA + DVI
		Power: 12 VDC External power supply 100-240 VAC 50-60Hz included

APPLICATIONS:












MECHANICAL DRAWING:







UNIT:mm