

# RUGGED COMPLETELY SEALED FULL IP66/NEMA4X STAINLESS STEEL

Chassis/Surface Mount, 43" Brightness 1000 nits based on Default 3 set waterproof connectors Waterproof connectors & cables: DVI, VGA & Power 6ft long only with external 100~240V AC + adapter Wide Temp -30 to 85C Operating Temp

Remark: This unit designed to be installed under completed shaded area without direct sunlight. Not facing east and west



## MODEL: CCHW4300HB-SIP

USB INPUT IS OPTIONAL FOR TOUCHSCREEN

### FEATURES:

- High Contrast color TFT LCD Monitor support resolution up to Full HD (1920x 1080 )
- Widely used in chemical industry, food industry, medical devices, appliances etc. with good corrosion resistance
- Full IP65 Stainless Design
- Universal Power adapter.
- Support DDC1 & DDC2B for Plug & Play compatibility.
- Advanced OSD control for picture quality adjustment

### SPECIFICATIONS:

Display	Viewing Size Image	43"
	Active Display Area (mm)	941.18 (H) x 529.42 (V)
	Pixel Pitch (mm)	0.4902(H)x 0.4902(V)
	Resolution	1920x1080
	Contrast Ratio	1100:1 (typ.)
	Color	16.7 M
	Brightness	1000 cd/m
	Viewing Angle	-89~89 (H) ; -89~89 (V)
	Recommended Resolution	1920 x 1080 @ 60Hz
	Signal Connector	VGA, DVI

Power	Source	100V~240VAC power cord
	Consumption	49.28W typical, normal operation
	Management	VESA DPMS Compliant
	Touch	Optional
Optional	High Brightness	1000,1500
	Auto Dimming	YES
	POWER in	DC24V
	Remote Control	YES
	IO	AV, HMI, DP

### IP65 Waterproof connectors:



VGA Input DVI Input USB Input Power Input  
(Option)

# MECHANICAL DRAWING

