

INDUSTRIAL OPEN FRAME LCD

6.5" 4:3 Open frame LCD Rear OSD with Rear Housing
700nits TFT LCD, 640x480,VGA + DVI Input

Model: COP0650



FEATURES:

- High Contrast color TFT LCD Monitor support resolution up to VGA(640x 480)
- Power management system conforms to VESA DPMS and EPA Energy Star standards.
- Full consideration for touch screen installation and application.
- Universal Power adapter.
- Support DDC1 & DDC2B for Plug & Play compatibility.
- Advanced OSD control for picture quality adjustment.
- Detachable stand for wall-mounting application.
- Heavy duty Monitor with steel frame.

SPECIFICATIONS:

Display	Viewing Size Image	6.5"
	Active Display Area (mm)	132.48(H)x99.36(V)
	Pixel Pitch (mm)	0.207(H)x0.207(V)
	Resolution	640x480
	Contrast Ratio	600:1 (typ.)
	Color	262,144(6bit+colors)
	Brightness	700 cd/m ²
	Viewing Angle	-80~80(H); -70~70(V) (typ.)
	Recommended Resolution	640x480@60HZ, 75HZ
	Signal Connector	VGA,DVI
Power	Source	12V DC in, with External AC-DC Adapter(100-240V)
	Consumption	15W typical, normal operation
	Management	VESA DPMS Compliant
Optional	Touch	Resistive, PCAP
	High Brightness	1000,1500
	Auto Dimming	YES
	POWER in	DC24V,DC9V~36V
	Remote Control	YES
	IO	AV,HDMI,DP

APPLICATIONS:



MECHANICAL DRAWING:

