

# INDUSTRIAL OPEN FRAME LCD

15" Open frame LCD Rear OSD with Rear Housing  
300nits TFT LCD, 1366x768, VGA + DVI Input

Model: COPW1560



## FEATURES:

- High Contrast color LCD Monitor with resolution up to(1366x768)
- Power management system conforms to VESA DPMS and EPA Energy Star standards.
- Full consideration for touch screen installation and application.
- Universal Power adapter.
- Support DDC1 & DDC2B for Plug & Play compatibility.
- Advanced OSD control for picture quality adjustment.
- Detachable stand for wall-mounting application.
- Heavy duty Monitor with steel frame.

## SPECIFICATIONS:

<b>Display</b>	Viewing Size Image	15.6"
	Active Display Area (mm)	344.232 (H) x 193.536 (V)
	Pixel Pitch (mm)	0.252x 0.252
	Resolution	1366x768
	Contrast Ratio	500 : 1 (typ.)
	Color	16.7M
	Brightness	300 cd/m <sup>2</sup>
	Viewing Angle	-85~85 (H) ; -80~80 (V)
	Recommended Resolution	1366 x 768 @ 60Hz, 75Hz
	Signal Connector	15 pin D-Sub
<b>Power</b>	Source	AC 100 ~ 240V, Universal,+/-10%
	Consumption	25W typical, normal operation
	Management	VESA DPMS Compliant
<b>Optional</b>	Touch	Resistive, PCAP ,IR
	High Brightness	1000,1500
	Auto Dimming	YES
	POWER in	DC24V,DC9V~36V
	Remote Control	YES
	IO	AV,HDMI,DP

## APPLICATIONS:



# MECHANICAL DRAWING:

