

INDUSTRIAL OPEN FRAME LCD

19" Wide Open frame LCD Rear OSD with Rear Housing
250nits TFT LCD, 1440x900, VGA + DVI Input

Model: COPW1900



FEATURES:

- High Contrast color LCD Monitor with resolution up to SXGA (1280x1024)
- Power management system conforms to VESA DPMS and EPA Energy Star standards.
- Full consideration for touch screen installation and application.
- Universal Power adapter.
- Support DDC1 & DDC2B for Plug & Play compatibility.
- Advanced OSD control for picture quality adjustment.
- Detachable stand for wall-mounting application.
- Heavy duty Monitor with steel frame.

SPECIFICATIONS:

Display	Viewing Size Image	18.95"
	Active Display Area (mm)	410.4(H) x 256.5 (V)
	Pixel Pitch (mm)	0.285 (H) x 0.285 (V)
	Resolution	1440 x 900
	Contrast Ratio	3000 : 1 (typ.)
	Color	16.2M (8bits/colors)
	Brightness	250 cd/m ²
	Viewing Angle	-89~89 (H) ; -89~89 (V)
	Recommended Resolution	1440x 1024 @ 60Hz
	Signal Connector	VGA,DVI
Power	Source	12V DC in with External AC-DC, Adapter(100-240V)
	Consumption	51W typical, normal operation
	Management	VESA DPMS Compliant
Optional	Touch	Resistive, PCAP ,IR
	High Brightness	1000,1500
	Auto Dimming	YES
	POWER in	DC24V,DC9V~36V
	Remote Control	YES
	IO	AV,HDMI,DP

APPLICATIONS:



MECHANICAL DRAWING:

