

# Floor Standing Portrait Kiosks

Single Sided outdoor rated 46" Floor Standing Portrait Kiosks Floor standing kiosk in portrait orientation with PCAP touch behind glass USB Controller

Model: CMKSS4600-PCAP



## FEATURES:

- IP56 rated Enclosures (No display)
- 14 gauge steel construction
- 4mm AR coated tempered safety glass
- Built in storage for housing media players and other integrated electronics
- Can be secured to the floor using pre-drilled holes in the base
- Equipped with heat exhaust fans to eliminate heat buildup caused by the display and/or integrated electronics
- 6-Way Surge Strip included
- PCAP touch behind glass USB Controller
- Made in USA-

### SUPERIOR COOLING

#### Two Fans

Equipped with heat exhaust fans to eliminate heat buildup caused by the display and/or integrated electronics.

### SECURE

#### Dual Steel Keyed Locks

Two steel keyed locks secure the dual back door compartment.

### VENTILATED

#### Air Intake

Vents positioned at bottom to direct airflow over components and display and out the top vented fans.

### POWER ACCESS

#### Internal Access

Internal access hole for conduit entry into cabinet.

### WEATHERPROOF

#### Covered Heat Exhaust

Protected heat exhaust cover keeps the elements out of the kiosk.

### COMPONENT SHELF

#### Secure Organized Storage

Easily attach components to adjustable shelf for secure ventilated placement.

### OPTIONAL ACCESS

#### Optional Knockouts

Knockouts to route power cables through on either side.



## LCD SPECIFICATIONS:

<b>Display</b>	Screen Size / Panel Technology		46" / S-VA, LED Backlit	
	Resolution / Brightness		1920x1080 (16:9) / 3,000 nits	
	Contrast Ratio		5,000:1	
	Viewing Angle (Horizontal/Vertical)		178°/178°	
	Orientation		Landscape / Portrait	
	Response Time (G-to-G)		6ms	
<b>Connectivity</b>	Input	RGB Video Audio	VGA (D-sub 15 pin), DVI-D, Display Port 1.2 HDMI1, HDMI2, HDBaseT(LAN Common) Stereo Mini Jack	
	Output	RGB Audio	Display Port 1.2 (Loop-out) Stereo Mini Jack	
	External Control		HDBaseT, RJ45	
	External Sensor		N/A	
	Power Supply (external)		AC 100 - 240 V~ (+/- 10 %), 50/60 Hz	
<b>Power</b>	Power Consumption (Typical/Max)		412W / 600W	
	Power Consumption (Standby)		< 0.5W	
	Operating Temperature		0°C~55°C	
<b>Environmental Conditions</b>	Humidity		10~80%	
	Special	IP56 Certified for Simple Enclosure Outdoor usage, Protection Glass(Anti Graffiti, Infrared Reduce), Polarized Sun Glasses Viewable in any direction, HD Base T for Long Distance Installalling, Portrait Installation Support, Button Lock, Lamp Error Detection, Auto Brightness Control with Ambient Brightness Sensor, Anti Image Retention, Temperature Sensor, Pivot Display, MagicInfo S, Smart Scheduling, RJ45 MDC, PIP/PBP, Auto Source Switching & Recovery		
<b>Features</b>	Wall Mount Interface		989.0 x 503.6 mm	
	24/7 Operation		Yes	
	<b>Dimensions</b>	Product Dimensions (without stand)		42.1" x 24.6" x 3.56" (Set)
		Packaging Dimensions		24.5" x 22.2" x 3.54" (Power Box)
Bezel Width (mm)		46.2" x 12.0" x 28.6" 24.9mm		
<b>Weight</b>	Product Weight / Shipping Weight		86.9 lbs. (Set), 18.9 lbs. (Power Box) / 119.7 lbs.	
<b>Green Management</b>	Emission Standard		Class A	
	ENERGY STAR® 6.0 Compliant		N/A	
	RoHS Compliant		Yes	
	Packaging Recyclability		Packing Materials Recyclable	

## MECHANICAL DRAWING:

