

ePower Product Line Card



Final CS P/N = Base Model P/N + Input Cord Option P/N

Base Model weight = ~6lbs

CS P/N	Type	Description	Output Voltage	Output Current	Input Voltage	Input Current per line (max)	Input Current per line (derated)	Capacity (max)	Capacity (derated)	LxWxD (inches)
2000047	Base Model	18 C13 outlets 6 C19 outlets		C13 (US/EU): 12A/10A; C19 (US/EU): 16A/16A						55.0x2.40x2.25
2000048	Base Model	21 C13 outlets 3 C19 outlets		C13 (US/EU): 12A/10A; C19 (US/EU): 16A/16A						55.0x2.40x2.25
2000049	Base Model	24 C13 outlets		C13 (US/EU): 12A/10A						55.0x2.40x2.25

Input Cord Option unit weight = ~2lbs

Input Cord (length = 8 feet)

CS P/N	Type	Description	Output Voltage	Output Current	Input Voltage	Input Current per line (max)	Input Current per line (derated)	Capacity (max)	Capacity (derated)	LxWxD (inches)
2000050	Input Cord Option	420P9W 20A 3P4W - Δ - 3φ	208VAC, 1φ, 60Hz		208VAC, Δ, 3φ, 60Hz	20 A	16 A	7.2 kW	5.8 kW	4.33x2.40x2.25
2000051	Input Cord Option	520P9W 20A 4P5W - Δ - 3φ	208VAC, 1φ, 60Hz		120/208VAC, Δ, 3φ, 60Hz	20 A	16 A	7.2 kW	5.8 kW	4.33x2.40x2.25
2000052	Input Cord Option	520P9W 20A 4P5W - Y - 3φ	120VAC, 1φ, 60Hz		120/208VAC, Y, 3φ, 60Hz	20 A	16 A	7.2 kW	5.8 kW	4.33x2.40x2.25
2000053	Input Cord Option	430P9W 30A 3P4W - Δ - 3φ	208VAC, 1φ, 60Hz		208VAC, Δ, 3φ, 60Hz	30 A	24 A	11 kW	8.7 kW	14.0x2.40x2.25
2000054	Input Cord Option	530P9W 30A 4P5W - Δ - 3φ	208VAC, 1φ, 60Hz		120/208VAC, Δ, 3φ, 60Hz	30 A	24 A	11 kW	8.7 kW	14.0x2.40x2.25
2000055	Input Cord Option	530P9W 30A 4P5W - Y - 3φ	120VAC, 1φ, 60Hz		120/208VAC, Y, 3φ, 60Hz	30 A	24 A	11 kW	8.7 kW	14.0x2.40x2.25
2000056	Input Cord Option	460P9W 60A 3P4W - Δ - 3φ	208VAC, 1φ, 60Hz		208VAC, Δ, 3φ, 60Hz	60 A	48 A	21.6 kW	17.3 kW	14.0x2.40x2.25
2000057	Input Cord Option	560P9W 60A 4P5W - Δ - 3φ	208VAC, 1φ, 60Hz		120/208VAC, Δ, 3φ, 60Hz	60 A	48 A	21.6 kW	17.3 kW	14.0x2.40x2.25
2000058	Input Cord Option	560P9W 60A 4P5W - Y - 3φ	120VAC, 1φ, 60Hz		120/208VAC, Y, 3φ, 60Hz	60 A	48 A	21.6 kW	17.3 kW	14.0x2.40x2.25
2000059	Input Cord Option	CS8365C 50A 3P4W - Δ - 3φ	208VAC, 1φ, 60Hz		208VAC, Δ, 3φ, 60Hz	50 A	40 A	18 kW	14.4 kW	14.0x2.40x2.25
2000060	Input Cord Option	IEC 60309 16A 3PNE - Y - 3φ	230VAC, 1φ, 50/60Hz		400/230VAC, Y, 3φ, 50/60Hz	16 A	16 A	11.0 kW	11.0 kW	4.33x2.40x2.25
2000061	Input Cord Option	IEC 60309 32A 3PNE - Y - 3φ	230VAC, 1φ, 50/60Hz		400/230VAC, Y, 3φ, 50/60Hz	32 A	32 A	22.1 kW	22.1 kW	14.0x2.40x2.25
2000062	Input Cord Option	IEC 60309 63A 3PNE - Y - 3φ	230VAC, 1φ, 50/60Hz		400/230VAC, Y, 3φ, 50/60Hz	63 A	63 A	43.5 kW	43.5 kW	14.0x2.40x2.25
2000063	Input Cord Option	NEMA L15-20P - Δ - 3φ	208VAC, 1φ, 60Hz		208VAC, Δ, 3φ, 60Hz	20 A	16 A	7.2 kW	5.8 kW	4.33x2.40x2.25
2000064	Input Cord Option	NEMA L15-30P - Δ - 3φ	208VAC, 1φ, 60Hz		208VAC, Δ, 3φ, 60Hz	30 A	24 A	11 kW	8.7 kW	14.0x2.40x2.25
2000065	Input Cord Option	NEMA L21-20P - Δ - 3φ	208VAC, 1φ, 60Hz		120/208VAC, Δ, 3φ, 60Hz	20 A	16 A	7.2 kW	5.8 kW	4.33x2.40x2.25
2000066	Input Cord Option	NEMA L21-20P - Y - 3φ	120VAC, 1φ, 60Hz		120/208VAC, Y, 3φ, 60Hz	20 A	16 A	7.2 kW	5.8 kW	4.33x2.40x2.25
2000067	Input Cord Option	NEMA L21-30P - Δ - 3φ	208VAC, 1φ, 60Hz		120/208VAC, Δ, 3φ, 60Hz	30 A	24 A	11 kW	8.7 kW	14.0x2.40x2.25
2000068	Input Cord Option	NEMA L21-30P - Y - 3φ	120VAC, 1φ, 60Hz		120/208VAC, Y, 3φ, 60Hz	30 A	24 A	11 kW	8.7 kW	14.0x2.40x2.25

Models w/o Circuit Breakers
Models w/ Circuit Breakers

Overall dimensions: Base + Input optio: 58.0x2.4x2.4
Overall dimensions: Base + Input optio: 67.8x2.4x2.8

