

INDUSTRIAL IP65 5 SIDES LCD MONITOR



Wide 10.1" LCD Monitor, 1280 x 800, LED- 800nits, BNC input x 1 and BNC output x 1, Wide temp -20 to + 60C, IP65 5 side fully sealed except the bottom with 3ft long cables with DC input 24VDC, 3ft long BNC input x 1 , 3ft long BNC output x 1. Direct Control + and - from the side OSD membrane.

Model: CSW1010WTIPBNC

FEATURES:

- High Contrast color LCD Monitor with resolution up (1280x800)
- Energy Star standards power management system.
- High Shock & Vibration Resistance
- Widely Application: Automation, Medical, Tourist, Transportation

SPECIFICATIONS:

Display	Viewing Size Image	10.1"
	Active Display Area (mm)	219 (H) x 138(V)
	Resolution	1280 x 800
	Contrast Ratio	500 : 1 (typ)
	Color	262K (RGB 6 Bit) 16.2M
	Viewing Angle	-85~85 (H) ; -85~85 (V)
	Brightness	800 cd/m2
	Recommended Resolution	1280 x 800@ 60Hz
	Signal Connector	BNC input x 1 and BNC output x 1
Power	Source	12V DC in, with External AC-DC, Adapter(100-240V)
	Consumption	10W typical, normal operation
	Management	VESA DPMS Compliant
Optional	Touch	Resistive, PCAP ,IR
	High Brightness	1000,1500
	Auto Dimming	YES
	POWER in	DC24V, DC9V~36V
	Remote Control	YES
	IO	AV,HDMI,DP

APPLICATIONS:



MECHANICAL DRAWING:

