

Highly Configurable Compact Panel Solutions

26"

32"

42"

46"

52"

46" in plan!

Because it has to be right

- PC / Media Player Integration
- Serial OSD -
Monitoring And Controlling
- 24 / 7 h Applications
- Glass / Touch Integration
- Sunlight Readable



Canvys started its new **CP** (compact panel) product line with 32" **PD-CP32AU** and 42" **PD-CP42AU**. Canvys now introduces to the market: 26" **PD-CP26CM** and 52" **PD-CP52**; 46" in plan.

The **CP series** is ideal for *Industrial and Digital Signage applications*.

All versions (besides 26") have an integrated "user platform" on the rear side. This enables the customers to integrate e.g. PC/media player or other own solutions. These robust displays are manufactured in Germany with high quality components and long availability.

*Configure your own **CP** display for your needs!*

PC / MP Integration

26"

32"

42"

46"

52"

46" in panel!



PC / Media Player Integration

The **CP series** enables the customer to integrate a PC or a Media Player.

Canvys provides a **standard** solution which will fit for mini PC's: DE45, Apple Mac, Fujitsu-Siemens Esprimo and Media Player: EYEZONE 1080P.

Due to a flexible basis plate all mentioned standard devices can be integrated very easily. The device, also the cables will be hidden behind cover sheets (PC cover sheet and cable channel) for a clean and attractive solution (see pictures).



32", backside, w/o option PC integration



32", backside, w/ PC mounted on basis plate, w/o mounted cover sheets (PC cover and cable channel)



32", backside, w/ PC mounted on basis plate, w/ mounted PC cover sheet



32", backside, w/ option PC integration

Canvys suggestions for integration:	DE45 mini PC	Apple Mac mini	Fujitsu-Siemens Esprimo mini PC
Chipset	Intel GM45	Intel 945GM	Intel GM45/GM47, Intel ICH9-M
Graphic chip	Intel GMA x4500MND	NVIDIA GeForce 9400M	Intel GMA 4500MHD
System memory	4 GB max	4 GB max	4 GB max
HDMI port	×1	×1	no
DVI port	no	×1	×1
Fan	yes	yes	yes

EYEZONE 1080P Media Player	
Memory	CF card
Resolution output	up to 1920 × 1080
Ethernet connector	RJ-45
HDMI port	×1
VGA port	×1
S-video port	×1

Also **customized** solutions are easy to implement in size of 200 × 300 × 55 mm, by using a different basis plate. Please contact therefore our sales field engineers.



Specifications and more features on page 3.

Specifications & Features

26"

32"

42"

46"

52"

46" in plan!

Serial OSD

Customers who already purchased the Canvys™ **LI series** in the past know Kontron's CRTtoLCD graphics controller which is now integrated in the **CP series** too. Canvys is able to realize for its customers their own boot-logos, sensors and many different interfaces. The displays can be monitored and controlled completely through a serial interface (RS232).

Customers can integrate the LCDs into a network by connecting them with a PC. Backlights and temperature can be controlled remotely.

24 / 7 h Usage

With the 24/7 h engineering approach and it's high quality metal case, the **CP series** is the best solution for *POS / POI, industrial, transportation and digital signage applications.*

Glass / Touch Integration

The **CP series** is available with protection glass for a rugged environment. For touch applications, Canvys integrates 3M touch screens ClearTekII™ or DST, for a precise and accurate touch (others upon request).



Option: VESA adapter flexible mounting system
VESA 200, many different mounting holes also for Rittal ceiling mount

Series Model / Type	CP Series 26" PD-CP26CM / 32" PD-CP32AU / 42" PD-CP42AU / 52" PD-CP52
Resolution	1920 × 1200 (26"), 1366 × 768 (32"), 1920 × 1080 (42" / 52")
Brightness (typ.)	> 350 cd/m ² w/o touch
Contrast ratio (typ.)	> 1500:1
I/O ports	D-Sub 15pin (analog), DVI-D optional: Video & S-Video
MTBF backlight	> 40,000 h
Options*	Customized colour and structure Chassis version for integration Touch screen, protection glass Optical bonded protection glass = sunlight readable Audio function Portrait panel PC/Media player integration (not standardized for 26") VESA adapter
Misc	High quality metal case unit Horizontal usage 24 / 7 h usage OSD RS232C serial interface
Approval	CE, EN 61000-6-3/6-1, 60950-1
Mounting	mounting holes (M4) on side and rear cover + optional VESA adapter
Power input Power supply approvals	110 - 230 VAC; safety regulations: UL60950-1/ 60601-1, CSA, CE, TUV EN60950-1/ 60601-1
Availability	Europe
<i>Detailed technical specifications upon request.</i>	

Sunlight Readable

By integration of a rugged bonded glass the display is readable under sunlight. The bonded glass enables a solution that highly reduces internal light reflections and refractions, maximizing the clarity of the display. The bonding process improves also the robustness of the display surface.



CP series w/ mounted VESA adapter
- rear view -

Horizontal Usage

Due to regulable fans a overheat control is guaranteed. The horizontal usage is ideal for integration in *gaming tables* or *marine applications.*



CP series w/ mounted VESA adapter - side view -
Adapter position angular (8.5° max),
possible to lock (anti-theft-protection)