DSX1500/DSX1700 Interactive Digital Signage Kiosks One Integrated Display

The ITechLCD Signage System's DSX1500/1700 offers an integrated computing display in one slim, mountable package. Ideal for digital signage and kiosk applications, this elegant all-in-one system can be remotely managed, and a Windows operating system makes it easy to integrate with other applications. This fully compatible solution of hardware and software, with touch and point-of-service options, offers efficient deployments. Bring dynamic interaction to your audience with the flexible DSX1500/1700; the future of interactive signage has arrived.

Key Features:

- Elegant all-in-one, slim, space saving design; efficient mounting
- Fan-less, high performance operation
- High contrast LCD panel with wide viewing angle
- Low power consumption
- IR touch screen option
- Optional magnetic card reader
- Web-based software for remote display management
- Web-based, centralized content management and distribution software
- Remote player monitoring, control, and upgrade



Specifications:

Display	15" (DSX1500) or 17" (DSX1700) TFT LCD					
Display	DSX1500: Up to 1024 x 768;					
Resolution	DSX1700: Up to 1280 x 1024					
Processor	1.5 GHz x86 processor					
Memory (RAM)	1GB					
Operating Systems	Windows® XP Embedded					
Storage	2GB, 4GB, 8GB or 16GB flash module; 2.5" HDD					
Display Enclosure	ABS + PC Plastic					
Base or Pedestal	Optional: Detachable aluminum construction; VESA- compliant mounting					
Control Buttons	Five (5) side buttons - Power (1) and Programmable (4)					
Input/Output Ports	Five (5) side buttons - Power (1) and Programmable (4)					
Stereo Speakers	Built-in speakers					
Network	Ethernet 10/100 MB Base-T LAN; 802.11a/b/g					
Interface	WLAN					
AC/DC Adapter	Input voltage 100~240V AC, 50/60 Hz; Output: 18.5V, 3.5A					
Power Cords	North America, EU, UK, China					

Dimensions (H x W x D)	DSX1500: 10.9 x 13.9 x 2.5 in, 278 x 354 x 63 mm; DSX1700: 12.6 x 15.3 x 2.7 in, 320 x 388 x 68 mm	
Weight	DSX1500: 10.58 lbs (4.8 Kg); DSX1700: 12.8 lbs (5.8 Kg)	
Regulatory	FCC Class B, CE, C-Tick, RoHS compliant	
Operating Temperature	0° C - 40° C	
Humidity	0% - 90% non-condensing	

Applications:

The DSX1500/1700 signage system is ideal for the following applications:

- Kiosk
- Retail
- Entertainment/ Gaming
- Education Manufacturing
- Finance
- Healthcare
- Hospitality
- Control and Monitoring



Content Manager:

ITechLCD Content Manager Software is one of the primary components in the comprehensive ITechLCD Signage System. This web-enabled server software provides central management of ITechLCD signage appliances as media players, and automates the design and distribution of a wide variety of multimedia file formats into playlists. Playlists are then set into schedules and stored in a central database for distribution to the network of signage appliances. With the ITechLCD Content Manager, the message to be played is assembled, scheduled, and delivered for dynamic playback over a network of appliances using standard file formats and protocols.

Device Manager:

ITechLCD Device Manager is a comprehensive software management tool to remotely manage networked iTechLCD appliances. It provides a web browser interface fronting a database management system which supports e.g., inventory, organize, control, update a network of ITechLCD signage appliances over the LAN, WAN, or wireless networks. The ITechLCD Device Manager utilizes "push and pull" technology to interact with remote appliances, allowing system administrators to inventory hardware, update applications and registry entries, shutdown / reboot / wake-up devices, update system firmware and software, along with access to advanced logging and scheduling capabilities.

Feature Highlights:

- Groups and Players
- Media Management
- Ticker
- Multiple-zones
- Preset Templates
- Playlists Scheduling
- Urgent Casts
- System Management
- Reporting
- Auto Recovery

Feature Highlights:

Client Inventory

Scheduling

WakeOnLan

File Package

History and Job Manager

Group Management

Appliance Shutdown

Image Management

BIOS Management

Database Support



VabDT		[Versine 5.5]						los ref				
	De	Device Manager										
	A	dients	M Retest	DiedkAll ClearAll		Search new clients		Each				
	96 0	dients.										
		Name	Description	P Address	Int	Secon	CManager	States				
	0	WETRICUL		66.100.100.55	CE-WET	CE-WEITSKOLK	86.100.100.2					
		WET-IEE-R		66.100.100.92	CE-WBT	CE-WEIT196	66.100.100.2					
		WETHER		66,100.100.76	CE-WET	CE-WEITING	66.100.100.2					
		WETNET.		66.100.100.75	CE-WET	CE-WEITING	66.100.100.2					
		WETHERE		66.100.100.74	CE-WST	CE-WEITING	66.100.100.2					
		WETHES		66.100.100.59	CE-WBT	CE-WEIT166	66.100.100.2					
		WETHERA		66.100.100.54	CE-WST	CE-WEITH6	66.100.100.2					
		WETHER-30		200.200.1.19	CE-WST	CE-WBF196	66.100.100.2					
		WETHERS		66.100.100.53	(E-W9T	CE-WBT196	66.100.100.2					
		WET166-28		200.200.1.21	CE-W9T	CE-WET166	86.100.100.2					
		WETHER 28		200.300.1.22	CE-WST	CE-WBI1166	6E 100 100.2					
		W87166-27		200.200.1.20	CE-W9T	CE-WET196	SE 100 100.2					
		WETHER 26		66.100.100.90	CE-W9T	CE-WBT166	66.100.100.2					
		WETHER 25		66.100.100.91	CE-WST	CE-WBIT166	86.100.100.2					
		WETHER-21		66.100.100.84	(E-W9T	CE-WBT196	66.108.100.2					

Major Options:

- Built-in 802.11a/b/g WLAN
- IR touch screen
- Magnetic card reader

* Options subject to change without notice.

Accessories:



Desktop Stand P/N: ACC-008-44signage

