

# DT-5K-MEM-TP

# **Membrane Keyboard with Touchpad**

The new DT-5K-MEM-TP is an industrial membrane keyboard built to withstand the harshest of environments. Modeled after iKey's popular 5K product line, this keyboard is manufactured with a hardcoated, textured polyester film and trampoline-mounted, snap-dome switches that provide a superior feel and a ctuation over a standard membrane keyboard. The integrated Synaptics touchpad is completely sealed under an extra layer of PVC membrane, which extends the life of the product. Since this keyboard lacks the crevices found between the keys of a regular keyboard, it is extremely durable and easy to clean. The DT-5K-MEM-TP is designed to meet NEMA 4X specifications, which means it can withstand directed hose water, disinfectants, environmental contaminants and heavy industrial use.



# **Technical Specifications**

Certifications NEMA 4X;IP67;UL60950;FCC Part 15 Class B;CE

Shock 3 x 11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections), or Single-

Cable USE

Key Switch MATERIAL: Hardcoated Textured Polyester Film LIFE: Greater Than 2 Million Cycles TRAVEL: 0.020 in. (0.5mm)

(Positively effected by Trampoline Mounting) ACTUATION FORCE: 9.88 oz +/- 1.06 oz (280g +/- 30g) FEEDBACK: Tactile

with Mechanical Snap

Vibration POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours

Power PS2: KEYBOARD: 40mA@5V (Keyboard port) TOUCHPAD: 10mA@5V (Mouse port) USB: 50mA@5V (CPU port)

Compatability PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems USB KEYBOARD/TOUCHPAD: All Windows and

Macintosh OS

Temperature Range STORAGE: -40C to +65C (-40F to +149F) OPERATING: 0C to +60C (32F to +140F)

Weight 5.25 lbs +/- 0.10 lbs (2.39 kg +/- 0.05 kg)

Warranty 1 year limited warranty

Humidity 100%

Dimensions 16.25" x 7.88" x 1.80" (w-h-d) 412.8mm x 200.2mm x 45.7 mm

Model Numbers DT-5K-MEM-TP-PS2: With PS/2 Cable DT-5K-MEM-TP-USB: With USB Cable

## **Features and Benefits**

10-Key Numeric Pad
 24 Function Keys

Hardcoated Textured Polyester Film
 Integrated Touchpad

Stainless Steel Case





DT-5K-MEM-TP

 DATE
 CHANGES
 REV

 04.23.08
 Original
 1.00

 05.01.08
 Updated Format
 1.01





**JWB** 

#### **KEY SWITCH**

MATERIAL: Hardcoated Textured Polyester Film LIFE: Greater Than 1 Million Cycles

TRAVEL: 0.020 in.

ACTUATION FORCE: 9.88 oz. +/- 1.06oz (280g +/- 30g)

FEEDBACK: Tactile with Mechanical Snap

#### **VIBRATION**

POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours

#### **POWER**

PS2: KEYBOARD: 40mA@5V (from Keyboard port) TOUCH PAD: 10mA@5V (from Mouse port)

USB: 50mA@5V (from CPU port)

#### **HUMIDITY**

100% Humidity Resistant

#### SHOCK

3 X 11 ms pulses of 50g on each of 3 axis

#### WEIGHT

5.25 lbs +/- 0.10 lbs (2.39 kg +/- 0.05 kg)

### TEMPERATURE RANGE

STORAGE: -40°F to +149°F (-40°C to +65°C) OPERATING: 32°F to +140°F (0°C to +60°C)

Part Number: DT-5K-MEM-TP	Drawing Number: MKT0100	Sheet: 1 OF 1
Drawing Title: DT-5K-MEM-TP-MKT	Revision: 1.01	Date: 05.01.08



i-Tech Company LLC

TOLL FREE: (888) 483-2418 • EMAIL: info@iTechLCD.com • WEB: www.iTechLCD.com