Ruggedized Tablet

for High Performance Mobile Computing

7" LED backlight capacitive touch display w/ quad-core 1.4GHz CPU and micro-SD card reader.



















The DVM700A Mobile POS Tablet features the integration of a brilliant 7" capacitive touch screen and a quad-core, energy efficient processor within a slim, lightweight and durable package. With Android 4.2 operating system, the DVM700A is easy to operate and to integrate with many applications. With built-in Wi-Fi and Bluetooth connection, as well as fully-integrated options such as RFID reader/ NFC, barcode scanner, MSR, and camera, this tablet offers seamless information capture for instant transmission on the sales floor, in the warehouse, in the restaurant, and in the field.

Features

- Slim, lightweight and durable
- 7" LED-backlight touch screen
- Support for Android 4.2 operating system
- Quad-core, 1.4GHz processor; high performance with low power consumption
- Built-in Wi-Fi and Bluetooth connection
- Optional camera, magnetic stripe reader, barcode scanner and RFID Reader/NFC

Major Options

- 5 megapixel back camera with LED flash, auto focus, white balance, gain control and exposure control
- 2D barcode scanner; reads both 1D and 2D barcodes, extremely durable, integrated for hassle-free operation
- RFID: HF/RFID 13.56MHz reader (ISO 15693 and 14443 A/B compliant)
- Magnetic stripe reader (MSR); triple track readers (ISO TK1, 2 & 3), high-performance decoding with ultra-compact design
- 3G module for HSPA+/WCDMA/EDGE/GPRS/GSM

Specifications

System		
CPU	Quad Core, 1.4GHz	
RAM	1GB	
Storage	8GB Flash	
Operating System	Android 4.2	
Display	7" LED-backlight screen with capacitive touch	
Display Resolution	1024 x 600	
TPM	N/A	
Fan/ Fanless	Fanless	
Control Switch and Buttons	1 power button and 1 trigger button	
Indicator	1 power/ battery status LED, 1 WLAN active LED and 1 MSR indicator	
Microphone	Built-in microphone	
Speaker	Built-in speaker	
Sensor	N/A	
Camera	Optional	
Network Interface		
WLAN	Wi-Fi 802.11a/b/g/n	
Bluetooth	Bluetooth 4.0 HS	
Mobile Broadband	3G WWAN (optional)	
I/O Ports		
USB Port	1 USB 2.0, 1 mini USB (with OTG function)	
Headset Jack	1 (2.5mm)	
DC-in	1	
Smart Card Reader	N/A	
SD Slot	1 Micro-SD card slot	



i-Tech Company LLC

TOLL FREE: (888) 483-2418 • EMAIL: info@iTechLCD.com • WEB: www.iTechLCD.com


Mechanical and Environmental		
AC/DC Adapter	Input: 100 – 240V AC; Output: 5V DC, 3A	
Battery Pack	Replaceable rechargeable Li-ion battery, 3.7V, 4000mAh	
Enclosure	ABS + PC plastics	
Stylus	Capacitive touch stylus	
Protective Bumpers	Rubber with handstrap (units with MSR have handstrap only)	
Dimensions (H x W x D)	5.24 x 8.75 x 0.7 in/ 133 x 210 x 18 mm	
Weight	1.1 lbs/ 0.5 kg	
IP Rating	N/A	
MIL-STD-810G	N/A	
EMI and EMC Tolerance	N/A	
Regulatory	FCC Class B, CE, RoHS compliant	
Temperature	Operation: 0°C – 50°C; Storage: -20°C – 60°C	
Humidity	0% – 90% non-condensing	
Major Options		
MSR	Triple track readers (ISO TK1, 2 & 3), JIS & AAMVA compliant	
Barcode Scanner	2D barcode scanner; reads 1D also	
Camera	5 megapixel back camera with LED flash	
RFID Reader	HF/RFID 13.56MHz reader (ISO 15693 and 14443 A/B compliant)	

I/O ports

Front View



Rear View



Side View



A. Magnetic stripe reader (Optional)	G. Micro-SD card reader	
B. Trigger button	H. Speaker	
C.Camera (Optional)	I. mini USB port	
D. LED Flash (Optional)	J. Headphone-out	
E. Power button	K. USB 2.0 port	
F. Battery switch	L. DC-in	



Accessories



StylusStylus for capacitive touch screen.



Coil Lanyard
Coil Lanyard for
Stylus, 3 pieces per



Cradle
Charging Cradle for
DT307SQ. Desktop
cradle with rear
pocket battery
charger. AC Power
adapter is not

included.

Desktop Charging



Battery Pack
Battery pack for
DVM700A. Hotswappable,
rechargeable Li-lon
battery pack.
Capacity: 4000mAh,
3.7V (14.8W).



4-Bay Gang
Charger
4-Bay Gang
Charger for
DT307SQ. Multi-bay
charger, capable of
charging up to 4
tablet devices
simultaneously.

