

The DVM700B mobile tablet features a 7" touchscreen in a compact and lightweight package. With on-screen soft keyboard, integrated Bluetooth connectivity, optional magnetic stripe reader, barcode scanner and RFID reader, the DVM700B enables efficient point-of-service/sale applications, inventory management, and field services.

Features

- Slim, lightweight and durable
- 7" LED-backlight touch screen
- Support for Microsoft® Windows® Mobile or CE operating system
- High performance with low power consumption
- Bluetooth and Wi-Fi connection

Major Options

- 3 megapixel back camera with LED flash, auto focus, white balance, gain control and exposure control
- 2D barcode scanner; reads both 1D and 2D barcodes, extremely durable, integrated for hassle-free operation
- RFID: HF/RFID 13.56MHz reader (ISO 15693 and 14443 A/B compliant)
- Magnetic stripe reader (MSR); triple track readers (ISO TK1, 2 & 3), high-performance decoding with ultra-compact design

System		
CPU	ARM 800MHz	
RAM	512MB	
Storage	4GB	
Operating System	Microsoft [®] Windows [®] CE 6.0; Windows [®] Mobile 6.5	
Display	7" LED-backlight screen with capacitive touch	
Display Resolution	800 x 480	
TPM	N/A	
Fan/ Fanless	Fanless	
Control Switch and Buttons	1 power button and 1 trigger button	
Indicator	1 power/ battery status LED, 1 WLAN active LED and 1 MSR indicator	
Microphone	Built-in microphone	
Speaker	Built-in speaker	
Sensor	N/A	
Camera	Optional	
Network Interface		
WLAN	Wi-Fi 802.11a/b/g/n	
Bluetooth	Bluetooth 2.1	
Mobile Broadband	N/A	
I/O Ports		
USB Port	1 USB 2.0, 1 mini USB	
Headset Jack	1 (2.5mm)	
DC-in	1	
Smart Card Reader	N/A	
SD Slot	1 Micro-SD card slot	

Specifications



Mechanical and Environmental		
AC/DC Adapter	Input: 100 – 240V AC; Output: 5V DC, 3A	
Battery Pack	3.7V, 4000mAh (hot-swappable)	
Enclosure	ABS + PC plastics	
Stylus	Capacitive touch stylus	
Protective Bumpers	Rubber with handstrap (units with MSR have handstrap only)	
Dimensions (H x W x D)	5.24 x 8.75 x 0.7 in/ 133 x 210 x 18 mm	
Weight	1.1 lbs/ 0.5 kg	
IP Rating	N/A	
MIL-STD-810G	N/A	
EMI and EMC Tolerance	N/A	
Regulatory	FCC Class B, CE, RoHS compliant	
Temperature	Operation: 0°C – 40°C; Storage: -20°C – 60°C	
Humidity	0% – 90% non-condensing	
Major Options		
MSR	Triple track readers (ISO TK1, 2 & 3), JIS & AAMVA compliant	
Barcode Scanner	2D barcode scanner; reads 1D also	
Camera	3 megapixel back camera with LED flash	
RFID Reader	HF 13.56MHz, ISO standard 15693, 14443A(B) & 18000-3 mode-1	

I/O ports







Front View

Side View



A. Magnetic stripe reader (Optional)	G. Micro-SD card reader
B. Trigger button	H. Speaker
C.Camera (Optional)	I. mini USB port
D. Flashlight (Optional)	J. Headphone-out
E. Power button	K. USB 2.0 port
F. Battery switch	L. DC-in



Accessories



Stylus Stylus for capacitive touch screen.



Coil Lanyard Coil Lanyard for Stylus, 3 pieces per kit.



Desktop Charging Cradle

Charging Cradle for DT307SQ. Desktop cradle with rear pocket battery charger. AC Power adapter is not included.



Battery Pack Battery pack for

DVM700B. Hotswappable, rechargeable Li-Ion battery pack. Capacity: 4000mAh, 3.7V (14.8W).



4-Bay Gang Charger

4-Bay Gang Charger for DT307SQ. Multi-bay charger, capable of charging up to 4 tablet devices simultaneously.

