

Provides industrial level input solution to optimize your space utilization by controlling your system in just 1U rack space.

Model: DKP120e-DVI-USB




## 1U Rackmount 20" LCD Console

### Features:

- Single rail easy to install and use
- Support Sun native resolution
- Support 18 various keyboard languages
- Bright Active Matrix TFT display
- OSD function (On Screen Display) for LCD display
- Durable keyboard (touchpad)
- Panel protected by tempered glass
- Support USB interface
- Support DVI interface
- Audio function (optional)
- DC power (optional)



### Applications:



### I/O Diagram



### Specifications:

System Connections	1	
Dimension	527.2 x 436.4 x 43.8 mm / 20.8 x 17.2 x 1.7	
Package Dimension	827 x 564 x 206 mm / 32.6 x 22.2 x 8.1 inches	
Net Weight	16.5 Kg / 36.4 lbs	
Gross Weight	22.5 Kg / 49.6 lbs	
Display Size	20.1 inches	
Panel Type	Active Matrix TFT LCD	
Resolution	Maximum Resolution up to 1600 x 1200	
Pixel Pitch	Supports 0.255 mm x 0.255 mm	
Viewing Angle (CR>10)	Right-Left view 178° (Typ) Up-Down	
Contrast Ratio	700 : 1	
Brightness	White 300 cd/m <sup>2</sup>	
Back Light	Six Lamps for Back Light	
Supported Colors	16.7M Colors (8-bit with FRC)	
Response Time	Rising Time 7 ms, Decay Time 9 ms	
Operating System	Dos, Windows (3.1, 9x, 2000, NT4, ME, XP, 2003 Server) Linux, Novell 3.12-6, HP UX,	
Connectors	PC Port	1 x VGA HDDB 15-pin 2 x PS/2 Mini Din 6-pin 2 x USB 1 x DVI, 1 x Audio line in (optional)
	Power	1 x DC jack
Signal Cable	KC-0303	
Keyboard Mouse	106 key PS/2 keyboard with touch pad	
Sync	45 - 80 KHz	
Power Source	100 - 240 VAC input	
Power Consumption	50W, 45W for Panel	
Temperature	Operate 0 ~ 50 °C / 32 ~ 122 °F Storage -20 ~ 60 °C / -4 ~	
Humidity	10% ~ 90% RH	
Chassis Construction	Heavy duty steel materials	
Keyboard Language	US, UK, German, French, Spanish, Italian, Portuguese, Dutch, Swiss, Belgium, Swedish, Norwegian, Danish, Japanese, Mandarin, Russian, Hebrew, Arabic	

Photo



Mechanical Drawing

