

# IntelliTouch Surface Wave

For High-Use Applications



## Applications

- Kiosks
- Ticketing machines
- Gaming machines
- Light industrial
- Office automation

**Elo's IntelliTouch touchscreens**, utilizing patented flat profile surface wave technology, are the picture-perfect, precision touch solution for high-use applications. The new flat profile technology has tiny transducers on the back of the touchscreen glass, eliminating the bumps on the front surface for a flatter integration solution. With the longest touchscreen warranty available, the IntelliTouch touchscreens are the preferred solution for applications requiring unsurpassed performance, reliability, and clarity. Their durable, pure-glass construction delivers the ultimate in image clarity and light transmission, preserves color purity, and works even if scratched. With their stable, drift-free operation, the IntelliTouch touchscreens guarantee a touch response that is on target. The IntelliTouch touchscreens are the ideal solution for kiosks, ticketing machines, gaming machines, light industrial, and office automation.

## Benefits

- Pure glass construction delivers the ultimate in image quality
- Stable, drift-free operation
- Continues to work even if scratched
- 10-year limited warranty

## IntelliTouch Surface Wave Specifications

### MECHANICAL

Input Method	Finger or gloved hand (cloth, leather, or rubber) activation
Available Sizes*	10.4" to 30"; visit our Web site for full specifications and other offerings

### ELECTRICAL

Positional Accuracy	Standard deviation of error is less than 0.080 in. (2 mm)
Resolution	Touchpoint density is based on controller resolution of 4096 x 4096, plus 255 levels corresponding to touch pressure
Touch Activation Force	Typically 2 to 3 ounces (55 to 85 grams)
Controller	Board: Serial (RS232) or USB 1.1

### OPTICAL

Light Transmission	Up to 90% per ASTM D 1003-92
--------------------	------------------------------

### ENVIRONMENTAL

Temperature	Operating: -20°C to 50°C Storage: -40°C to 71°C
Relative Humidity	Operating: 40°C at 90% RH, noncondensing
Altitude	Operating: 10,000 ft (3,048 m) Storage/transport: 50,000 ft (15,240 m)
Chemical Resistance	The touch active area of the touchscreen is resistant to chemicals that do not affect glass, such as: acetone, toluene, methyl ethyl ketone, isopropyl alcohol, methyl alcohol, ethyl acetate, ammonia-based glass cleaners, gasoline, kerosene, vinegar
Electrostatic Protection	Per EN 61000-4-2, 1995: Meets Level 4 (15 kV air/8 kV contact discharges)
Agency Approvals	UL, cUL, TÜV, CE, FCC Class A
Sealability	Can be sealed to meet NEMA 3/3R/5/12/12K/13, IP64 standards

### DURABILITY

Surface Durability	Surface durability is that of glass, Mohs' hardness rating of 7
Expected Life	No known wear-out mechanism, as there are no layers, coatings, or moving parts. IntelliTouch technology has been operationally tested to more than 50 million touches in one location without failure, using a stylus similar to a finger.
Warranty	Touchscreen: 10-year limited warranty Controller: 5-year limited warranty

\*Available in most standard sizes. For some sizes, transducers are located on a beveled edge or the front of the glass. See the touchscreen component drawing for details.



2701 dual serial/USB controller



Flat profile cable